



C410C123G3G5TA Information

Heisener.com

Part Number C410C123G3G5TA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 0.012UF 25V C0G AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C410C123G3G5TA Specifications

Manufacturer Part Number C410C123G3G5TA Manufacturer KEMET Category Capacitors Package Axial Series Aximax 400 Capacitance 0.012μF Tolerance ±2% Voltage - Rated 25V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Spacing - Lead Style -		
Category Capacitors Package Axial Series Aximax 400 Capacitance 0.012μF Tolerance ±2% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	C410C123G3G5TA
Package Axial Series Aximax 400 Capacitance 0.012 μF Tolerance ±2% Voltage - Rated 25 V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	KEMET
Package Axial Series Aximax 400 Capacitance 0.012μF Tolerance ±2% Voltage - Rated 25V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Category	Capacitors
Series Aximax 400 Capacitance 0.012μF Tolerance ±2% Voltage - Rated 25V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 0.012µF Tolerance ±2% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial
Tolerance ±2% Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Lead Style	Series	Aximax 400
Voltage - Rated Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) Thickness (Max) - Lead Spacing - Lead Style - COG, NP0 CO	Capacitance	0.012μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - COG, NPO COG, NPO COG, NPO COG, NPO Avial - Low ESL Bypass, Decoupling - Hough Hole - Axial - COG, NPO - Low ESL Avial - Low ESL - Now ESL - Avial - Lead Spacing - Lead Style	Tolerance	±2%
Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style55°C ~ 125°C Low ESL - Low ESL55°C ~ 125°C - 12	Voltage - Rated	25V
Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Case -	Operating Temperature	-55°C ~ 125°C
Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Features	Low ESL
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Lead Style	Ratings	-
Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style	Applications	Bypass, Decoupling
Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.095" Dia x 0.170" L (2.41mm x 4.32mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

C410C123G3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C410C123G3G5TA Payment Methods



















C410C123G3G5TA Shipping Methods













If you have any question about C410C123G3G5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com