



C410C209C3G5TA Information

Heisener.com

Part Number C410C209C3G5TA

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 2PF 25V C0G AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C410C209C3G5TA Specifications

Manufacturer C410C209C3G5TA Manufacturer KEMET Category Capacitors Package Axial Series Aximax 400 Capacitance 2pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Spacing - Lead Style -		
Category Capacitors Package Axial Series Aximax 400 Capacitance 2pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	C410C209C3G5TA
Package Axial Series Aximax 400 Capacitance 2pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	KEMET
PackageAxialSeriesAximax 400Capacitance2pFTolerance±0.25pFVoltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Category	Capacitors
Series Aximax 400 Capacitance 2pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 2pF Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial
Tolerance ±0.25pF Voltage - Rated 25V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Series	Aximax 400
Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Capacitance	2pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Tolerance	±0.25pF
Operating Temperature-55°C ~ 125°CFeaturesLow ESLRatings-ApplicationsBypass, DecouplingFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.095" Dia x 0.170" L (2.41mm x 4.32mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Voltage - Rated	25V
Features Low ESL Ratings - Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Maxing - Case	Operating Temperature	-55°C ~ 125°C
Applications Bypass, Decoupling Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Features	Low ESL
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Ratings	-
Mounting Type Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style Through Hole Axial 0.095" Dia x 0.170" L (2.41mm x 4.32mm) - Lead Style	Applications	Bypass, Decoupling
Package / Case Axial Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.095" Dia x 0.170" L (2.41mm x 4.32mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.095" Dia x 0.170" L (2.41mm x 4.32mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

C410C209C3G5TA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C410C209C3G5TA Payment Methods



















C410C209C3G5TA Shipping Methods













If you have any question about C410C209C3G5TA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com