



C48-10R20-41S7-102 Information

Heisener.com

For Reference Only

Part Number C48-10R20-41S7-102

Manufacturer Cinch Connectivity Solutions

Category

Connectors, Interconnects **Circular Connectors**

Description

CONN RCPT FMALE 41POS GOLD CRIMP

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









C48-10R20-41S7-102 Specifications

Manufacturer Part NumberC48-10R20-41S7-102ManufacturerCinch Connectivity SolutionsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26500, C48Connector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientation7Ingress ProtectionEnvironment SealedShell Material, FinishAluminum, AnodizedContact FinishGoldFeatures-Voltage - Rated-Current Rating-		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-26500, C48Connector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientation7Ingress ProtectionEnvironment SealedShell Material, FinishAluminum, AnodizedContact FinishGoldFeatures-Voltage - Rated-Current Rating-	Manufacturer Part Number	C48-10R20-41S7-102
Package-SeriesMIL-DTL-26500, C48Connector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientation7Ingress ProtectionEnvironment SealedShell Material, FinishAluminum, AnodizedContact FinishGoldFeatures-Voltage - Rated-Current Rating-	Manufacturer	Cinch Connectivity Solutions
Package-SeriesMIL-DTL-26500, C48Connector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientation7Ingress ProtectionEnvironment SealedShell Material, FinishAluminum, AnodizedContact FinishGoldFeatures-Voltage - Rated-Current Rating-	Category	Connectors, Interconnects
SeriesMIL-DTL-26500, C48Connector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientation7Ingress ProtectionEnvironment SealedShell Material, FinishAluminum, AnodizedContact FinishGoldFeatures-Voltage - Rated-Current Rating-		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions41Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientation7Ingress ProtectionEnvironment SealedShell Material, FinishAluminum, AnodizedContact FinishGoldFeatures-Voltage - Rated-Current Rating-	Package	-
Number of Positions41Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientation7Ingress ProtectionEnvironment SealedShell Material, FinishAluminum, AnodizedContact FinishGoldFeatures-Voltage - Rated-Current Rating-	Series	MIL-DTL-26500, C48
Shell Size - Insert20-41Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientation7Ingress ProtectionEnvironment SealedShell Material, FinishAluminum, AnodizedContact FinishGoldFeatures-Voltage - Rated-Current Rating-	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Bayonet Lock Orientation 7 Ingress Protection Environment Sealed Shell Material, Finish Aluminum, Anodized Contact Finish Gold Features - Voltage - Rated Current Rating - Current Rating	Number of Positions	41
Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeBayonet LockOrientation7Ingress ProtectionEnvironment SealedShell Material, FinishAluminum, AnodizedContact FinishGoldFeatures-Voltage - Rated-Current Rating-	Shell Size - Insert	20-41
Termination Crimp Fastening Type Bayonet Lock Orientation 7 Ingress Protection Environment Sealed Shell Material, Finish Aluminum, Anodized Contact Finish Gold Features - Voltage - Rated - Current Rating -	Shell Size, MIL	-
Fastening Type Orientation Togress Protection Shell Material, Finish Contact Finish Contact Finish Features Voltage - Rated Current Rating Fastening Type Bayonet Lock 7 Ingress Protection Fenvironment Sealed Aluminum, Anodized Gold	Mounting Type	Panel Mount, Flange
Orientation 7 Ingress Protection Environment Sealed Shell Material, Finish Aluminum, Anodized Contact Finish Gold Features - Voltage - Rated - Current Rating -	Termination	Crimp
Ingress Protection Environment Sealed Shell Material, Finish Aluminum, Anodized Contact Finish Gold Features - Current Rating - Current Rating	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features - Voltage - Rated Current Rating - Aluminum, Anodized Gold	Orientation	7
Contact Finish Gold Features - Voltage - Rated - Current Rating -	Ingress Protection	Environment Sealed
Features - Voltage - Rated - Current Rating -	Shell Material, Finish	Aluminum, Anodized
Voltage - Rated - Current Rating -	Contact Finish	Gold
Current Rating -	Features	-
	Voltage - Rated	-
	Current Rating	-
Report errors?		Report errors?

C48-10R20-41S7-102 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

C48-10R20-41S7-102 Payment Methods



















C48-10R20-41S7-102 Shipping Methods













If you have any question about C48-10R20-41S7-102, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com