

Heisener.com

CA02COME20-29PA176

CA02COME20-29PA176 Information

Part Number CA02COME20-29PA176

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 17POS BOX MNT W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA02COME20-29PA176 Specifications

| Manufacturer Part NumberCA02COME20-29PA176ManufacturerITT Cannon, LLCCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COMConnector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A | | |
|---|--------------------------|--|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CA-COMConnector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A | Manufacturer Part Number | CA02COME20-29PA176 |
| Package-SeriesMIL-DTL-5015, CA-COMConnector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A | Manufacturer | ITT Cannon, LLC |
| Package-SeriesMIL-DTL-5015, CA-COMConnector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A | Category | Connectors, Interconnects |
| Series MIL-DTL-5015, CA-COM Connector Type Receptacle, Male Pins Number of Positions 17 Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A | | Circular Connectors |
| Connector TypeReceptacle, Male PinsNumber of Positions17Shell Size - Insert20-29Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Zinc Die Cast, Nickel PlatedContact FinishGoldFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating22A | Package | - |
| Number of Positions Shell Size - Insert 20-29 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Features Voltage - Rated 500VAC, 700VDC Current Rating 22A | Series | MIL-DTL-5015, CA-COM |
| Shell Size - Insert 20-29 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A | Connector Type | Receptacle, Male Pins |
| Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A | Number of Positions | 17 |
| Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A | Shell Size - Insert | 20-29 |
| Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A | Shell Size, MIL | - |
| Fastening Type Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A | Mounting Type | Panel Mount, Flange |
| Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A | Termination | Solder Cup |
| Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Zinc Die Cast, Nickel Plated Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A | Fastening Type | Threaded |
| Shell Material, Finish Contact Finish Gold Features Voltage - Rated Current Rating Aluminum Alloy, Zinc Die Cast, Nickel Plated Gold 500VAC, 700VDC 22A | Orientation | N (Normal) |
| Contact Finish Gold Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A | Ingress Protection | IP65 - Dust Tight, Water Resistant |
| Features - Voltage - Rated 500VAC, 700VDC Current Rating 22A | Shell Material, Finish | Aluminum Alloy, Zinc Die Cast, Nickel Plated |
| Voltage - Rated 500VAC, 700VDC Current Rating 22A | Contact Finish | Gold |
| Current Rating 22A | Features | - |
| | Voltage - Rated | 500VAC, 700VDC |
| Report errors? | Current Rating | 22A |
| | | Report errors? |

CA02COME20-29PA176 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA02COME20-29PA176 Payment Methods





















CA02COME20-29PA176 Shipping Methods













If you have any question about CA02COME20-29PA176, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com