



CA3102R32-A47SF80 Information

Heisener.com

Part Number CA3102R32-A47SF80 **Manufacturer** ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 47 POS BOX MNT W/SKTS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CA3102R32-A47SF80 Specifications

| Manufacturer Part Number Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Receptacle, Female Sockets Number of Positions 47 Shell Size - Insert 32-A47 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Voltage - Rated 50V Current Rating 22A Receptacle, A47 Shell Size, MIL - Report errors? | | |
|---|--------------------------|---|
| CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-5015, CAConnector TypeReceptacle, Female SocketsNumber of Positions47Shell Size - Insert32-A47Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A | Manufacturer Part Number | CA3102R32-A47SF80 |
| Circular Connectors Package - Series MIL-DTL-5015, CA Connector Type Receptacle, Female Sockets Number of Positions 47 Shell Size - Insert 32-A47 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features - Voltage - Rated 50V Current Rating 22A | Manufacturer | ITT Cannon, LLC |
| Package - MIL-DTL-5015, CA Connector Type Receptacle, Female Sockets Number of Positions 47 Shell Size - Insert 32-A47 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A | Category | Connectors, Interconnects |
| Series MIL-DTL-5015, CA Connector Type Receptacle, Female Sockets Number of Positions 47 Shell Size - Insert 32-A47 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A | | Circular Connectors |
| Connector TypeReceptacle, Female SocketsNumber of Positions47Shell Size - Insert32-A47Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A | Package | - |
| Number of Positions Shell Size - Insert 32-A47 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Voltage - Rated 50V Current Rating 22A | Series | MIL-DTL-5015, CA |
| Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A | Connector Type | Receptacle, Female Sockets |
| Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A | Number of Positions | 47 |
| Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeatures-Voltage - Rated50VCurrent Rating22A | Shell Size - Insert | 32-A47 |
| Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A | Shell Size, MIL | - |
| Fastening Type Threaded Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A | Mounting Type | Panel Mount, Flange |
| Orientation N (Normal) Ingress Protection IP65 - Dust Tight, Water Resistant Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A | Termination | Crimp |
| Ingress Protection IP65 - Dust Tight, Water Resistant Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated Current Rating 22A | Fastening Type | Threaded |
| Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features - Voltage - Rated 50V Current Rating 22A | Orientation | N (Normal) |
| Contact Finish Features Voltage - Rated Current Rating Silver - 22A | Ingress Protection | IP65 - Dust Tight, Water Resistant |
| Features - Voltage - Rated 50V Current Rating 22A | Shell Material, Finish | Aluminum Alloy, Olive Drab Cadmium Plated |
| Voltage - Rated 50V Current Rating 22A | Contact Finish | Silver |
| Current Rating 22A | Features | - |
| | Voltage - Rated | 50V |
| Report errors? | Current Rating | 22A |
| * | | Report errors? |

CA3102R32-A47SF80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CA3102R32-A47SF80 Payment Methods



















CA3102R32-A47SF80 Shipping Methods













If you have any question about CA3102R32-A47SF80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com