



## CA3106E28A16PB06 Information

Heisener.com

Part Number CA3106E28A16PB06 Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG 9POS INLINE W/PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# CA3106E28A16PB06 Specifications

Manufacturer Part Number       CA3106E28A16PB06         Manufacturer       ITT Cannon, LLC         Category       Connectors, Interconnects         Circular Connectors         Package       -         Series       MIL-DTL-5015, CA-B         Connector Type       Plug, Male Pins         Number of Positions       9         Shell Size - Insert       28-A16         Shell Size, MIL       -         Mounting Type       Free Hanging (In-Line)         Termination       Solder Cup         Fastening Type       Reverse Bayonet Lock         Orientation       N (Normal)         Ingress Protection       IP67 - Dust Tight, Waterproof         Shell Material, Finish       Aluminum Alloy, Olive Drab Cadmium Plated         Contact Finish       Silver         Features       Shrink Boot Adapter         Voltage - Rated       50V         Current Rating       22A, 135A         Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-5015, CA-B Connector Type Plug, Male Pins Number of Positions 9 Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Features Shrink Boot Adapter Voltage - Rated Current Rating 22A, 135A	Manufacturer Part Number	CA3106E28A16PB06
Package-SeriesMIL-DTL-5015, CA-BConnector TypePlug, Male PinsNumber of Positions9Shell Size - Insert28-A16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating22A, 135A	Manufacturer	ITT Cannon, LLC
Package - MIL-DTL-5015, CA-B Connector Type Plug, Male Pins Number of Positions 9 Shell Size - Insert 28-A16 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 222A, 135A	Category	Connectors, Interconnects
Series MIL-DTL-5015, CA-B Connector Type Plug, Male Pins Number of Positions 9 Shell Size - Insert 28-A16 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A, 135A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions9Shell Size - Insert28-A16Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeReverse Bayonet LockOrientationN (Normal)Ingress ProtectionIP67 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Olive Drab Cadmium PlatedContact FinishSilverFeaturesShrink Boot AdapterVoltage - Rated50VCurrent Rating22A, 135A	Package	-
Number of Positions  Shell Size - Insert  28-A16  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Features  Shrink Boot Adapter  Voltage - Rated  50V  Current Rating  22A, 135A	Series	MIL-DTL-5015, CA-B
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Reverse Bayonet Lock  Orientation  N (Normal)  Ingress Protection  IP67 - Dust Tight, Waterproof  Shell Material, Finish  Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Shrink Boot Adapter  Voltage - Rated  50V  Current Rating  22A, 135A	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter  Voltage - Rated 50V Current Rating 22A, 135A	Number of Positions	9
Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Reverse Bayonet Lock  Orientation N (Normal)  Ingress Protection IP67 - Dust Tight, Waterproof  Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated  Contact Finish Silver  Features Shrink Boot Adapter  Voltage - Rated 50V  Current Rating 22A, 135A	Shell Size - Insert	28-A16
Termination Solder Cup Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A, 135A	Shell Size, MIL	-
Fastening Type Reverse Bayonet Lock Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A, 135A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated 50V Current Rating 22A, 135A	Termination	Solder Cup
Ingress Protection IP67 - Dust Tight, Waterproof Shell Material, Finish Aluminum Alloy, Olive Drab Cadmium Plated Contact Finish Silver Features Shrink Boot Adapter Voltage - Rated Current Rating 22A, 135A	Fastening Type	Reverse Bayonet Lock
Shell Material, Finish  Contact Finish  Silver  Features  Shrink Boot Adapter  Voltage - Rated  Current Rating  Aluminum Alloy, Olive Drab Cadmium Plated  Silver  Shrink Boot Adapter  22A, 135A	Orientation	N (Normal)
Contact Finish Silver Shrink Boot Adapter Voltage - Rated Current Rating 22A, 135A	Ingress Protection	IP67 - Dust Tight, Waterproof
Features Shrink Boot Adapter  Voltage - Rated 50V  Current Rating 22A, 135A	Shell Material, Finish	Aluminum Alloy, Olive Drab Cadmium Plated
Voltage - Rated 50V Current Rating 22A, 135A	Contact Finish	Silver
Current Rating 22A, 135A	Features	Shrink Boot Adapter
-	Voltage - Rated	50V
Report errors?	Current Rating	22A, 135A
		Report errors?

#### CA3106E28A16PB06 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### CA3106E28A16PB06 Payment Methods



















## CA3106E28A16PB06 Shipping Methods













If you have any question about CA3106E28A16PB06, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com