

CENB1010A0549N01

CENB1010A0549N01 Information

Heisener.com	Part Number Manufacturer Category Description Package	CENB1010A0549N01 SL Power Electronics Manufacture of Condor/Ault Brands Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC/DC DESKTOP ADAPTER 5V 10W	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CENB1010A0549N01 Specifications

Manufacturer Part Number CENB 1010A0549N01 Manufacturer SL Power Electronics Manufacture of Condor/Ault Brands Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters AC DC Desktop, Wall Adapters Package - Series CENB 1010 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 55°C Output Connector Say: "L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series CENB1010 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input I00 ~ 240 VAC Voltage - Output (Max) 2A Power (Watts) I0W No Load Power Consumption 300mW (Max) Applications - Applications ITE (Commercial) Operating Temperature 0°C ~ 55°C Output Connector Power DNIN, 4 Pin Size / Dimension 3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Manufacturer Part Number	CENB1010A0549N01
AC DC Desktop, Wall Adapters Package - Series CENB1010 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output (Max) 2A Power (Watts) 100W No Load Power Consumption 300mW (Max) Polarization - Applications IE (Commercial) Efficiency Cevel V Operating Temperature 0°C ~ 5°C Output Connector Power DIN, 4 Pin Size / Dinension 3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands
Package-SeriesCENB1010Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output (Max)5VCurrent - Output (Max)2APower (Watts)00mW (Max)No Load Power Consumption-Polarization-ApplicationsITE (Conmercial)EfficiencyLevel VOperating Temperature0°C ~ 55°COutput ConnectorSall" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Category	Power Supplies - External/Internal (Off-Board)
Series CENB1010 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Voltage - Output 5V Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (commercial) Efficiency Level V Operating Temperature 0°C ~ 55°C Output Connector Power DIN, 4 Pin Size / Dimension 3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)2APower (Watts)10WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 55°COutput ConnectorPower DIN, 4 PinSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 55°C Output Connector Power DIN, 4 Pin Size / Dimension 3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Series	CENB1010
Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 5V Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 55°C Output Connector Power DIN, 4 Pin Size / Dimension 3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Region Utilized	International
Voltage - Input100 ~ 240 VACVoltage - Output5VCurrent - Output (Max)2APower (Watts)10WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 55°COutput ConnectorPower DIN, 4 PinSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Form	Desktop (Class II)
Voltage - Output5VCurrent - Output (Max)2APower (Watts)10WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 55°COutput ConnectorPower DIN, 4 PinSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 2A Power (Watts) 10W No Load Power Consumption 300mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 55°C Output Connector Power DIN, 4 Pin Size / Dimension 331" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts)10WNo Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 55°COutput ConnectorPower DIN, 4 PinSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Voltage - Output	5V
No Load Power Consumption300mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 55°COutput ConnectorPower DIN, 4 PinSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Current - Output (Max)	2A
Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 55°COutput ConnectorPower DIN, 4 PinSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Power (Watts)	10W
ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 55°COutput ConnectorPower DIN, 4 PinSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	No Load Power Consumption	300mW (Max)
EfficiencyLevel VOperating Temperature0°C ~ 55°COutput ConnectorPower DIN, 4 PinSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Polarization	-
Operating Temperature0°C ~ 55°COutput ConnectorPower DIN, 4 PinSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Applications	ITE (Commercial)
Output ConnectorPower DIN, 4 PinSize / Dimension3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Efficiency	Level V
Size / Dimension 3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)	Operating Temperature	0° C ~ 55°C
	Output Connector	Power DIN, 4 Pin
Report errors?	Size / Dimension	3.31" L x 1.85" W x 1.27" H (84.0mm x 47.0mm x 32.3mm)
		Report errors?

CENB1010A0549N01 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CENB1010A0549N01 Payment Methods



If you have any question about CENB1010A0549N01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com