

CENB1121A1565Q01

CENB1121A1565Q01 Information

	Part Number	CENB1121A1565Q01	
Contraction Com	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands	NARCE
	Category	Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters	
	Description	AC/DC DESKTOP ADAPTER 15V 120W	100 14 Maria
	Package	-	
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



CENB1121A1565Q01 Specifications

Manufacturer Part NumberCENB1121A1565Q01Manufacturer O Condor/Ault BrandsCategoryFower Supplies - External/Internal (Off-Board)CategoryAC DC Desktop, Wall AdaptersPackage-SeriesCENT1120Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input15VCurrent - Output (Max)8APower (Watts)120WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)Efficiency0°C ~ 40°COutput ConnectorStriped, Tinned Wire LeadsSize / DimensionSize / Size		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesCENT1120Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output (Max)8APower (Watts)100W (Max)Polarization-ApplicationsSOmW (Max)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorSa; "L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)	Manufacturer Part Number	CENB1121A1565Q01
AC DC Desktop, Wall AdaptersPackage-SeriesCENT1120Region UtilizedInternationalFormDesktop (Class II)FormCord (Sold Separately)Notage - Input100 ~ 240 VACVoltage - Output15VCurrent - Output (Max)8APower (Watts)100W (Max)No Load Power Consumption500W (Max)Polarization-ApplicationsEvel VEfficiencyCerce VOperating Temperature0° ~ 40°COutput ConnectorSias" L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)	Manufacturer	SL Power Electronics Manufacture of Condor/Ault Brands
Package-SeriesCENT1120Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output15VCurrent - Output (Max)8APower (Watts)120WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dinension8.36" L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)	Category	Power Supplies - External/Internal (Off-Board)
Series CENT120 Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 15V Current - Output (Max) 8A Power (Watts) 120W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Striped, Tinned Wire Leads Size / Dimension 8.36" L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input100 ~ 240 VACVoltage - Output15VCurrent - Output (Max)8APower (Watts)120WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorSa;" L x 2.65" W x 1.74" H (212.4mm x 47.4mm x 44.3mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 15V Current - Output (Max) 8A Power (Watts) 120W No Load Power Consumption 50mW (Max) Polarization - Applications IE (Commercial) Operating Temperature 0°C ~ 40°C Output Connector Stipped, Tinned Wire Leads Size / Dimension 8.36" L x 2.65" W x 1.74" H (212.4mm x 44.3mm)	Series	CENT1120
Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 15V Current - Output (Max) 8A Power (Watts) 120W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Stripped, Tinned Wire Leads Size / Dimension 8.36" L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)	Region Utilized	International
Voltage - Input100 ~ 240 VACVoltage - Output15VCurrent - Output (Max)8APower (Watts)120WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension8.36" L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)	Form	Desktop (Class II)
Voltage - Output15VCurrent - Output (Max)8APower (Watts)120WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension8.36" L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)	Input Type	Cord (Sold Separately)
Current - Output (Max)8APower (Watts)120WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension8.36" L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts)120WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension8.36" L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)	Voltage - Output	15V
No Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension8.36" L x 2.65" W x 1.74" H (212.4mm x 44.3mm)	Current - Output (Max)	8A
Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension8.36" L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)	Power (Watts)	120W
ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension8.36" L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)	No Load Power Consumption	500mW (Max)
EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension8.36" L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)	Polarization	-
Operating Temperature0°C ~ 40°COutput ConnectorStripped, Tinned Wire LeadsSize / Dimension8.36" L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)	Applications	ITE (Commercial)
Output ConnectorStripped, Tinned Wire LeadsSize / Dimension8.36" L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)	Efficiency	Level V
Size / Dimension 8.36" L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)	Operating Temperature	0° C ~ 40° C
	Output Connector	Stripped, Tinned Wire Leads
Report errors?	Size / Dimension	8.36" L x 2.65" W x 1.74" H (212.4mm x 67.4mm x 44.3mm)
		Report errors?

CENB1121A1565Q01 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

CENB1121A1565Q01 Payment Methods





If you have any question about CENB1121A1565Q01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com