



CEO100M200 Information

For Reference Only

Part Number CEO100M200

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 100A 415VAC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

Request a Quote E-mail: salesdept@heisener.com



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CEO100M200 Specifications

Manufacturer Part NumberCEO100M200ManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesCEOFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC415VVoltage Rating - DC-Response Time-ApplicationsElectrical, Industrial, Motor ProtectionFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.850" L (31.00mm x 47.00mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesCEOFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC415VVoltage Rating - DC-Response Time-ApplicationsElectrical, Industrial, Motor ProtectionFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.850" L (31.00mm x 47.00mm)	Manufacturer Part Number	CEO100M200
PackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesCEOFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC415VVoltage Rating - DC-Response Time-ApplicationsElectrical, Industrial, Motor ProtectionFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.850" L (31.00mm x 47.00mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesCEOFuse TypeCartridgeCurrent Rating100AVoltage Rating - AC415VVoltage Rating - DC-Response Time-ApplicationsElectrical, Industrial, Motor ProtectionFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.850" L (31.00mm x 47.00mm)	Category	Circuit Protection
Series CEO Fuse Type Cartridge Current Rating 100A Voltage Rating - AC 415V Voltage Rating - DC - Response Time - Applications Electrical, Industrial, Motor Protection Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case CIEO Size / Dimension 1.220" Dia x 1.850" L (31.00mm x 47.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC415VVoltage Rating - DC-Response Time-ApplicationsElectrical, Industrial, Motor ProtectionFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 1.850" L (31.00mm x 47.00mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 415V Voltage Rating - DC Response Time - Applications Electrical, Industrial, Motor Protection Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 100A 100A 100A 100A 100A 100A 100A 10	Series	CEO
Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial, Motor Protection Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 415V Approvals - Cless Approvals - Class - Clas	Fuse Type	Cartridge
Voltage Rating - DC Response Time Applications Electrical, Industrial, Motor Protection Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Class - Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.850" L (31.00mm x 47.00mm)	Current Rating	100A
Response Time - Applications Electrical, Industrial, Motor Protection Features - Class - Clas	Voltage Rating - AC	415V
Applications Electrical, Industrial, Motor Protection Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.850" L (31.00mm x 47.00mm)	Voltage Rating - DC	-
Features - Class - Class - Coperating Temperature - Seraking Capacity @ Rated Voltage 80kA Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.850" L (31.00mm x 47.00mm)	Response Time	-
Class - Approvals - Class - Coperating Temperature - Streaking Capacity @ Rated Voltage 80kA Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.850" L (31.00mm x 47.00mm)	Applications	Electrical, Industrial, Motor Protection
Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.850" L (31.00mm x 47.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.850" L (31.00mm x 47.00mm)	Class	-
Breaking Capacity @ Rated Voltage 80kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.850" L (31.00mm x 47.00mm)	Approvals	-
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.850" L (31.00mm x 47.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 1.850" L (31.00mm x 47.00mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 1.220" Dia x 1.850" L (31.00mm x 47.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.220" Dia x 1.850" L (31.00mm x 47.00mm)
		Report errors?

CEO100M200 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CEO100M200 Payment Methods



















CEO100M200 Shipping Methods













If you have any question about CEO100M200, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com