



CJT1001K8JJ Information

Heisener.com

Part Number CJT1001K8JJ

Manufacturer TE Connectivity Passive Product

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 1.8K OHM 5% 100W

Package Rectangular Case

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CJT1001K8JJ Specifications

Manufacturer Part Number CJT1001K8JJ Manufacturer TE Connectivity Passive Product Category Resistors Package Rectangular Case Series CJT, CGS Resistance 1.8 kOhms Tolerance ±5% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 6.496" L x 1.575" W (165.00mm x 40.00mm) Height - Seated (Max) 0.787" (20.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -		
Category Resistors Package Rectangular Case Series CJT, CGS Resistance 1.8 kOhms Tolerance ±5% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 6.496" L x 1.575" W (165.00mm x 40.00mm) Height - Seated (Max) 0.787" (20.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Manufacturer Part Number	CJT1001K8JJ
Package Rectangular Case Series CJT, CGS Resistance 1.8 kOhms Tolerance ±5% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 6.496" L x 1.575" W (165.00mm x 40.00mm) Height - Seated (Max) 0.787" (20.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Manufacturer	TE Connectivity Passive Product
PackageRectangular CaseSeriesCJT, CGSResistance1.8 kOhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension6.496" L x 1.575" W (165.00mm x 40.00mm)Height - Seated (Max)0.787" (20.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Category	Resistors
SeriesCJT, CGSResistance1.8 kOhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension6.496" L x 1.575" W (165.00mm x 40.00mm)Height - Seated (Max)0.787" (20.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-		Chassis Mount Resistors
Resistance1.8 kOhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±440ppm/°COperating Temperature-Features-Coating, Housing TypeAluminumMounting FeatureFlangesSize / Dimension6.496" L x 1.575" W (165.00mm x 40.00mm)Height - Seated (Max)0.787" (20.00mm)Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Package	Rectangular Case
Tolerance ±5% Power (Watts) 100W Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 6.496" L x 1.575" W (165.00mm x 40.00mm) Height - Seated (Max) 0.787" (20.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Series	CJT, CGS
Power (Watts) Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 6.496" L x 1.575" W (165.00mm x 40.00mm) Height - Seated (Max) Lead Style Wire Leads Package / Case Failure Rate - 100W Mirewound ±440ppm/°C - - - 0.787" (20.00mm) Wire Leads Rectangular Case Failure Rate - - 100W Wirewound ±440ppm/°C - - - - - - - - - - - - -	Resistance	1.8 kOhms
Composition Wirewound Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 6.496" L x 1.575" W (165.00mm x 40.00mm) Height - Seated (Max) 0.787" (20.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Tolerance	±5%
Temperature Coefficient ±440ppm/°C Operating Temperature - Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 6.496" L x 1.575" W (165.00mm x 40.00mm) Height - Seated (Max) 0.787" (20.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Power (Watts)	100W
Operating Temperature Features Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 6.496" L x 1.575" W (165.00mm x 40.00mm) Height - Seated (Max) 0.787" (20.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 6.496" L x 1.575" W (165.00mm x 40.00mm) Height - Seated (Max) 0.787" (20.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Temperature Coefficient	±440ppm/°C
Coating, Housing Type Aluminum Mounting Feature Flanges Size / Dimension 6.496" L x 1.575" W (165.00mm x 40.00mm) Height - Seated (Max) 0.787" (20.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Operating Temperature	-
Mounting Feature Flanges Size / Dimension 6.496" L x 1.575" W (165.00mm x 40.00mm) Height - Seated (Max) 0.787" (20.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Features	-
Size / Dimension 6.496" L x 1.575" W (165.00mm x 40.00mm) Height - Seated (Max) 0.787" (20.00mm) Lead Style Wire Leads Package / Case Rectangular Case Failure Rate -	Coating, Housing Type	Aluminum
Height - Seated (Max) Lead Style Package / Case Rectangular Case Failure Rate 0.787" (20.00mm) Wire Leads Rectangular Case	Mounting Feature	Flanges
Lead StyleWire LeadsPackage / CaseRectangular CaseFailure Rate-	Size / Dimension	6.496" L x 1.575" W (165.00mm x 40.00mm)
Package / Case Rectangular Case Failure Rate -	Height - Seated (Max)	0.787" (20.00mm)
Failure Rate -	Lead Style	Wire Leads
	Package / Case	Rectangular Case
Report errors?	Failure Rate	-
		Report errors?

CJT1001K8JJ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CJT1001K8JJ Payment Methods





















CJT1001K8JJ Shipping Methods













If you have any question about CJT1001K8JJ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com