

CMF551M9000BER6

CMF551M9000BER6 Information

	Part Number	CMF551M9000BER6	
	Manufacturer	Vishay Dale	
www.stalberty.com	Category	Resistors Through Hole Resistors	
	Description	RES 1.9M OHM 1/2W 0.1% AXIAL	- 11.2
	Package	Axial	- AND
		For the pricing/inventory/lead time, please contact us	121294
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



a Quote

CMF551M9000BER6 Specifications

Manufacturer Part NumberCMF551M9000BER6ManufacturerVishay DaleCategoryResistorsPackageThrough Hole ResistorsPackageAxialSeriesCMFResistance1.9 MOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WFeaturesFlame Retardant Coating, Moisture Resistant, SafetyFeatures525pm/°COperating Temperature55°C ~ 175°CPackage / CaseAxial
CategoryResistorsFackageAxialPackageCMFResistance1.9 MOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionHeat FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyPoperating Temperature-55°C ~ 175°C
FindThrough Hole ResistorsPackageAxialSeriesCMFResistance1.9 MOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°C
PackageAxialSeriesCMFResistance1.9 MOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°C
SeriesCMFResistance1.9 MOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 175°C
Resistance1.9 MOhmsTolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°C
Tolerance±0.1%Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 175°C
Power (Watts)0.5W, 1/2WCompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 175°C
CompositionMetal FilmFeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25ppm/°COperating Temperature-55°C ~ 175°C
FeaturesFlame Retardant Coating, Moisture Resistant, SafetyTemperature Coefficient±25pm/°COperating Temperature-55°C ~ 175°C
Temperature Coefficient±25ppm/°COperating Temperature-55°C ~ 175°C
Operating Temperature $-55^{\circ}C \sim 175^{\circ}C$
Package / Case Axial
Supplier Device Package Axial
Size / Dimension 0.090" Dia x 0.240" L (2.29mm x 6.10mm)
Height - Seated (Max) -
Number of Terminations 2
Failure Rate -
Report errors ²

CMF551M9000BER6 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

CMF551M9000BER6 Payment Methods



If you have any question about CMF551M9000BER6, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com