



CPPLC5-HT76T Information



For Reference Only

Part Number CPPLC5-HT76T

Manufacturer Cardinal Components Inc.

Category Crystals, Oscillators, Resonators

Programmable Oscillators

Description OSC PROG CMOS 5V TRI ST 100PPM

Package 4-SMD, No Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CPPLC5-HT76T Specifications

Manufacturer CPPLCS-HT76T Manufacturer Cardinal Components Inc. Category Crystals, Oscillators, Resonators Package 4-SMD, No Lead Series FIPO? CPPL Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range IMHz ~ 133MHz Function Enable/Disable Output CMOS Voltage - Supply 5V Frequency Stability ±100ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size (Dispersions) 1.07% Mod 126 W 45 (00 cm m 2.20 cm m)		
Category Crystals, Oscillators, Resonators Programmable Oscillators Package 4-SMD, No Lead Series FIPO? CPPL Type XO (Standard) Programmable Type Programmable Type Programmable Frequency Range IMHz ~ 133MHz Function Enable/Disable Output CMOS Voltage - Supply 5V Frequency Stability #100ppm Frequency Stability (Total) - Operating Temperature Spread Spectrum Bandwidth - Current - Supply (Max) Astings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Manufacturer Part Number	CPPLC5-HT76T
Package4-SMD, No LeadSeriesFIPO? CPPLTypeXO (Standard)Programmable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 133MHzFunctionEnable/DisableOutputCMOSVoltage - Supply5VFrequency Stability±100ppmFrequency Stability (Total)-Operating Temperature-40°C ~ 85°CSpread Spectrum Bandwidth-Current - Supply (Max)45mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No Lead	Manufacturer	Cardinal Components Inc.
Package4-SMD, No LeadSeriesFIPO? CPPLTypeXO (Standard)Programmable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 133MHzFunctionEnable/DisableOutputCMOSVoltage - Supply5VFrequency Stability±100ppmFrequency Stability (Total)-Operating Temperature-40°C ~ 85°CSpread Spectrum Bandwidth-Current - Supply (Max)45mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No Lead	Category	Crystals, Oscillators, Resonators
SeriesFIPO? CPPLTypeXO (Standard)Programmable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 133MHzFunctionEnable/DisableOutputCMOSVoltage - Supply5VFrequency Stability±100ppmFrequency Stability (Total)-Operating Temperature-40°C ~ 85°CSpread Spectrum Bandwidth-Current - Supply (Max)45mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No Lead		Programmable Oscillators
Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 133MHz Function Enable/Disable Output CMOS Voltage - Supply 5V Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 40°C ~ 85°D, No Lead	Package	4-SMD, No Lead
Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 133MHz Function Enable/Disable Output CMOS Voltage - Supply 5V Frequency Stability ±100ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Series	FIPO? CPPL
Available Frequency Range1MHz ~ 133MHzFunctionEnable/DisableOutputCMOSVoltage - Supply5VFrequency Stability±100ppmFrequency Stability (Total)-Operating Temperature-40°C ~ 85°CSpread Spectrum Bandwidth-Current - Supply (Max)45mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No Lead	Type	XO (Standard)
Function Enable/Disable Output CMOS Voltage - Supply 5V Frequency Stability ±100ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Programmable Type	Programmed as Request
Output CMOS Voltage - Supply 5V Frequency Stability ±100ppm Frequency Stability (Total) - Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Available Frequency Range	1MHz ~ 133MHz
Voltage - Supply5VFrequency Stability±100ppmFrequency Stability (Total)-Operating Temperature-40°C ~ 85°CSpread Spectrum Bandwidth-Current - Supply (Max)45mARatings-Mounting TypeSurface MountPackage / Case4-SMD, No Lead	Function	Enable/Disable
Frequency Stability (Total) Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case ±100ppm -40°C ~ 85°C -40°C ~ 85°C -40°C ~ 85°C -40°C ~ 85°C -45mA -45mA -45mA -45mA -45mA -45mA -45mA	Output	CMOS
Frequency Stability (Total) Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Voltage - Supply	5V
Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Frequency Stability	±100ppm
Spread Spectrum Bandwidth - Current - Supply (Max) 45mA Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Frequency Stability (Total)	-
Current - Supply (Max) Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Operating Temperature	-40°C ~ 85°C
Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Spread Spectrum Bandwidth	-
Mounting Type Surface Mount Package / Case 4-SMD, No Lead	Current - Supply (Max)	45mA
Package / Case 4-SMD, No Lead	Ratings	-
-	Mounting Type	Surface Mount
0.10711 - 0.12611 W (5.00	Package / Case	4-SMD, No Lead
Size / Dimension 0.197 L x 0.126 W (5.00mm x 5.20mm)	Size / Dimension	0.197" L x 0.126" W (5.00mm x 3.20mm)
Height 0.051" (1.30mm)	Height	0.051" (1.30mm)
Report errors?		Report errors?

CPPLC5-HT76T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CPPLC5-HT76T Payment Methods





















CPPLC5-HT76T Shipping Methods













If you have any question about CPPLC5-HT76T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com