



CPPLT4-LT0PT Information



For Reference Only

Part Number CPPLT4-LT0PT

Manufacturer Cardinal Components Inc.

Category Crystals, Oscillators, Resonators

Programmable Oscillators

DescriptionOSC PROG TTL 3.3V TRI ST 50PPMPackage8-DIP, 4 Leads (Half Size, Metal Can)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CPPLT4-LT0PT Specifications

Manufacturer Part Number CPPLT4-LTOPT Manufacturer Cardinal Components Inc. Category Crystals, Oscillators, Resonators Package 8-DIP, 4 Leads (Half Size, Metal Can) Series FIPO? CPPL Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range IMHz ~ 100MHz Function Enable/Disable Output TTL Voltage - Supply 3.3V Frequency Stability ±50ppm Frequency Stability (Total) - Operating Temperature 0°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 25mA Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height Depart were**		
Category Crystals, Oscillators, Resonators Package 8-DIP, 4 Leads (Half Size, Metal Can) Series FIPO? CPPL Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 100MHz Function Enable/Disable Output TTL Voltage - Supply 3.3V Frequency Stability ±50ppm Frequency Stability (Total) - Operating Temperature 0°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 25mA Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)	Manufacturer Part Number	CPPLT4-LT0PT
Package 8-DIP, 4 Leads (Half Size, Metal Can) Series FIPO? CPPL Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 100MHz Function Enable/Disable Output TTL Voltage - Supply 3.3V Frequency Stability (Total) - Operating Temperature 0°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 25mA Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 1.20m Size / S	Manufacturer	Cardinal Components Inc.
Package 8-DIP, 4 Leads (Half Size, Metal Can) Series FIPO? CPPL Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 100MHz Function Enable/Disable Output TTL Voltage - Supply 3.3V Frequency Stability ±50ppm Frequency Stability (Total) - Operating Temperature 0°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 25mA Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)	Category	Crystals, Oscillators, Resonators
Series FIPO? CPPL Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 100MHz Function Enable/Disable Output TTL Voltage - Supply 3.3V Frequency Stability ±50ppm Frequency Stability (Total) - Operating Temperature 0°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 25mA Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)		Programmable Oscillators
TypeXO (Standard)Programmable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 100MHzFunctionEnable/DisableOutputTTLVoltage - Supply3.3VFrequency Stability±50ppmFrequency Stability (Total)-Operating Temperature0°C ~ 70°CSpread Spectrum Bandwidth-Current - Supply (Max)25mARatings-Mounting TypeThrough HolePackage / Case8-DIP, 4 Leads (Half Size, Metal Can)Size / Dimension0.520" L x 0.520" W (13.20mm x 13.20mm)Height0.220" (5.60mm)	Package	8-DIP, 4 Leads (Half Size, Metal Can)
Programmable Type Programmed as Request Available Frequency Range 1MHz ~ 100MHz Function Enable/Disable Output TTL Voltage - Supply 3.3V Frequency Stability ±50ppm Frequency Stability (Total) - Operating Temperature 0°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 25mA Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)	Series	FIPO? CPPL
Available Frequency Range Function Enable/Disable Output TTL Voltage - Supply 3.3V Frequency Stability ±50ppm Frequency Stability (Total) - Operating Temperature 0°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 25mA Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.220" (5.60mm)	Туре	XO (Standard)
Function Enable/Disable Output TTL Voltage - Supply 3.3V Frequency Stability ±50ppm Frequency Stability (Total) - Operating Temperature 0°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 25mA Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)	Programmable Type	Programmed as Request
Output TTL Voltage - Supply 3.3V Frequency Stability ±50ppm Frequency Stability (Total) - Operating Temperature 0°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 25mA Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.220" (5.60mm)	Available Frequency Range	1MHz ~ 100MHz
Voltage - Supply 3.3V Frequency Stability Frequency Stability (Total) Operating Temperature O°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.220" (5.60mm) 3.3V ±50ppm - N°C ~ 70°C STRA - Current - Supply (Max) 25mA - Through Hole 8-DIP, 4 Leads (Half Size, Metal Can) 0.520" L x 0.520" W (13.20mm x 13.20mm)	Function	Enable/Disable
Frequency Stability (Total) Operating Temperature O°C ~ 70°C Spread Spectrum Bandwidth Current - Supply (Max) Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.220" (5.60mm)	Output	TTL
Frequency Stability (Total) Operating Temperature 0°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)	Voltage - Supply	3.3V
Operating Temperature 0°C ~ 70°C Spread Spectrum Bandwidth - Current - Supply (Max) 25mA Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)	Frequency Stability	±50ppm
Spread Spectrum Bandwidth Current - Supply (Max) Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)	Frequency Stability (Total)	-
Current - Supply (Max) Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)	Operating Temperature	0°C ~ 70°C
Ratings Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)	Spread Spectrum Bandwidth	-
Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)	Current - Supply (Max)	25mA
Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)	Ratings	-
Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.220" (5.60mm)	Mounting Type	Through Hole
Height 0.220" (5.60mm)	Package / Case	8-DIP, 4 Leads (Half Size, Metal Can)
	Size / Dimension	0.520" L x 0.520" W (13.20mm x 13.20mm)
Deport among	Height	0.220" (5.60mm)
Report errors?		Report errors?

CPPLT4-LT0PT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CPPLT4-LT0PT Payment Methods



















CPPLT4-LT0PT Shipping Methods













If you have any question about CPPLT4-LT0PT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com