

CR4420-150 Information

Heisener.com

Part Number CR4420-150

Manufacturer CR Magnetics Inc.

Category Sensors, Transducers
Current Transducers

Description SENSOR CURRENT XFMR 150A AC

Package Module

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









CR4420-150 Specifications

Manufacturer CR4420-150 Category Sensors, Transducers Package Module Series CR4400 For Measuring AC Sensor Type Transformer w/Conditioning Current - Sensing 150A Number of Channels 1 Output Ratiometric, 4mA ~ 20mA Sensitivity - Frequency 50Hz ~ 400kHz Linearity - Accuracy ±0.5% Voltage - Supply 24V Response Time 250ms Current - Supply (Max) 45mA Operating Temperature 0°C ~ 60°C Polarization Bidirectional Mounting Type DIN Rail, Panel Package / Case Module	M. C., D. W. I	CD 4400 150
Category Sensors, Transducers Package Module Series CR4400 For Measuring AC Sensor Type Transformer w/Conditioning Current - Sensing 150A Number of Channels 1 Output Ratiometric, 4mA ~ 20mA Sensitivity - Frequency 50Hz ~ 400kHz Linearity - Accuracy ±0.5% Voltage - Supply 24V Response Time 250ms Current - Supply (Max) 45mA Operating Temperature 0°C ~ 60°C Polarization Bidirectional Mounting Type DIN Rail, Panel Package / Case Module	Manufacturer Part Number	CR4420-150
Package Module Series CR4400 For Measuring AC Sensor Type Transformer w/Conditioning Current - Sensing 150A Number of Channels 1 Output Ratiometric, 4mA ~ 20mA Sensitivity - Frequency 50Hz ~ 400kHz Linearity - Accuracy ±0.5% Voltage - Supply 24V Response Time 250ms Current - Supply (Max) 45mA Operating Temperature 0°C ~ 60°C Polarization Bidirectional Mounting Type DIN Rail, Panel Package / Case Module	Manufacturer	_
Package Module Series CR4400 For Measuring AC Sensor Type Transformer w/Conditioning Current - Sensing 150A Number of Channels 1 Output Ratiometric, 4mA ~ 20mA Sensitivity - Frequency 50Hz ~ 400kHz Linearity - Accuracy ±0.5% Voltage - Supply 24V Response Time 250ms Current - Supply (Max) 45mA Operating Temperature 0°C ~ 60°C Polarization Bidirectional Mounting Type DIN Rail, Panel Package / Case Module	Category	Sensors, Transducers
Series CR4400 For Measuring AC Sensor Type Transformer w/Conditioning Current - Sensing 150A Number of Channels 1 Output Ratiometric, 4mA ~ 20mA Sensitivity - Frequency 50Hz ~ 400kHz Linearity - Accuracy ±0.5% Voltage - Supply 24V Response Time 250ms Current - Supply (Max) 45mA Operating Temperature 0°C ~ 60°C Polarization Bidirectional Mounting Type DIN Rail, Panel Package / Case Module		Current Transducers
For Measuring AC Sensor Type Transformer w/Conditioning Current - Sensing 150A Number of Channels 1 Output Ratiometric, 4mA ~ 20mA Sensitivity - Frequency 50Hz ~ 400kHz Linearity - Accuracy ±0.5% Voltage - Supply 24V Response Time 250ms Current - Supply (Max) 45mA Operating Temperature 0°C ~ 60°C Polarization Bidirectional Mounting Type DIN Rail, Panel Package / Case Module	Package	Module
Sensor TypeTransformer w/ConditioningCurrent - Sensing150ANumber of Channels1OutputRatiometric, 4mA ~ 20mASensitivity-Frequency50Hz ~ 400kHzLinearity-Accuracy±0.5%Voltage - Supply24VResponse Time250msCurrent - Supply (Max)45mAOperating Temperature0°C ~ 60°CPolarizationBidirectionalMounting TypeDIN Rail, PanelPackage / CaseModule	Series	CR4400
Current - Sensing 150A Number of Channels 1 Output Ratiometric, 4mA ~ 20mA Sensitivity - Frequency 50Hz ~ 400kHz Linearity - Accuracy ±0.5% Voltage - Supply 24V Response Time 250ms Current - Supply (Max) 45mA Operating Temperature 0°C ~ 60°C Polarization Bidirectional Mounting Type DIN Rail, Panel Package / Case Module	For Measuring	AC
Number of Channels1OutputRatiometric, 4mA ~ 20mASensitivity-Frequency50Hz ~ 400kHzLinearity-Accuracy±0.5%Voltage - Supply24VResponse Time250msCurrent - Supply (Max)45mAOperating Temperature0°C ~ 60°CPolarizationBidirectionalMounting TypeDIN Rail, PanelPackage / CaseModule	Sensor Type	Transformer w/Conditioning
Output Ratiometric, 4mA ~ 20mA Sensitivity - Frequency 50Hz ~ 400kHz Linearity - Accuracy ±0.5% Voltage - Supply 24V Response Time 250ms Current - Supply (Max) 45mA Operating Temperature 0°C ~ 60°C Polarization Bidirectional Mounting Type DIN Rail, Panel Package / Case Module	Current - Sensing	150A
Sensitivity - Frequency 50Hz ~ 400kHz Linearity - Accuracy ±0.5% Voltage - Supply 24V Response Time 250ms Current - Supply (Max) 45mA Operating Temperature 0°C ~ 60°C Polarization Bidirectional Mounting Type DIN Rail, Panel Package / Case Module	Number of Channels	1
Frequency 50Hz ~ 400kHz Linearity - Accuracy ±0.5% Voltage - Supply 24V Response Time 250ms Current - Supply (Max) 45mA Operating Temperature 0°C ~ 60°C Polarization Bidirectional Mounting Type DIN Rail, Panel Package / Case Module	Output	Ratiometric, 4mA ~ 20mA
Linearity - Accuracy ±0.5% Voltage - Supply 24V Response Time 250ms Current - Supply (Max) 45mA Operating Temperature 0°C ~ 60°C Polarization Bidirectional Mounting Type DIN Rail, Panel Package / Case Module	Sensitivity	-
Accuracy ±0.5% Voltage - Supply 24V Response Time 250ms Current - Supply (Max) 45mA Operating Temperature 0°C ~ 60°C Polarization Bidirectional Mounting Type DIN Rail, Panel Package / Case Module	Frequency	50Hz ~ 400kHz
Voltage - Supply24VResponse Time250msCurrent - Supply (Max)45mAOperating Temperature0°C ~ 60°CPolarizationBidirectionalMounting TypeDIN Rail, PanelPackage / CaseModule	Linearity	-
Response Time 250ms Current - Supply (Max) 45mA Operating Temperature 0°C ~ 60°C Polarization Bidirectional Mounting Type DIN Rail, Panel Package / Case Module	Accuracy	±0.5%
Current - Supply (Max) Operating Temperature 0°C ~ 60°C Polarization Bidirectional Mounting Type DIN Rail, Panel Package / Case Module	Voltage - Supply	24V
Operating Temperature0°C ~ 60°CPolarizationBidirectionalMounting TypeDIN Rail, PanelPackage / CaseModule	Response Time	250ms
Polarization Bidirectional Mounting Type DIN Rail, Panel Package / Case Module	Current - Supply (Max)	45mA
Mounting Type DIN Rail, Panel Package / Case Module	Operating Temperature	0°C ~ 60°C
Package / Case Module	Polarization	Bidirectional
	Mounting Type	DIN Rail, Panel
Report errors?	Package / Case	Module
		Report errors?

CR4420-150 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

CR4420-150 Payment Methods





















CR4420-150 Shipping Methods













If you have any question about CR4420-150, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com