

DDMMY50PA101

est a Quote

DDMMY50PA101 Information

	DDMMY50PA101 ITT Cannon, LLC Connectors, Interconnects
	Connectors, Interconnects
ategory	,
	D-Sub Connectors
Description Package	CONN D-SUB PLUG 50POS PNL MNT
	-
	For the pricing/inventory/lead time, please contact
For Reference Only	us
	Website: https://www.heisener.com E-mail: salesdept@heisener.com
	-

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DDMMY50PA101 Specifications

Manufacturer Part Number DDMMY50PA101 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects D-Sub Connectors D-Sub Connectors Package - Series MIL-DTL-24308, D*MM Connector Style D-Sub Connectors Connector Type Plug, Male Pins Number of Positions 50 Number of Rows 3 Shell Size, Connector Layout 5 (DD, D) Contact Type Signal Mounting Type Panel Mount Flange Feature Solder Cup Features - Shell Material, Finish Steel, Yellow Chromate Plated Cadmium Contact Finish Gold Contact Finish Thickness Solpin (1.27µm) Ingress Protection - Material Flanmability Rating UL94 V-0		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions50Number of Rows3Shell Size, Connector LayoutSignalMunting TypePanel MountFlange FeatureSolder CupFreminationSolder CupFlanger FaituresSider CupShell Material, FinishStel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish ThicknessSojin (1.27µm)Ingress ProtectionJug Yellow Chromate Plated CadmiumIngress ProtectionSup Yellow Chromate Plated CadmiumIngress Plate	Manufacturer Part Number	DDMMY50PA101
PackageD-Sub ConnectorsPackage-SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions50Number of Rows3Shell Size, Connector Layout5(DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)Features-Shell Material, FinishStel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness-Ingress Protection-Metrial Flammability RatingUL94 V-0	Manufacturer	ITT Cannon, LLC
Package-SeriesML-DTL-24308, D*MMConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions50Number of Rows3Shell Size, Connector LayoutS(DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)Features-Shell Material, FinishStel Yellow Chromate Plated CadmiumContact FinishSider CupContact Finish ThicknessSolid (12µm)Ingress Protection-Material Flammability RatingU54 Vel	Category	Connectors, Interconnects
SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions50Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureSolder CupFeaturesSolder CupFeaturesSeel, Yellow Chromate Plated CadmiumContact FinishGoldContact FinishSipui (1.27µm)Ingress Protection-Material Flanmability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions50Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)Features> Solder CupFeaturesStel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish ThicknessSupin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions50Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	MIL-DTL-24308, D*MM
Number of Positions50Number of Rows3Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact Finish50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows3Number of Rows5 (DD, D)Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish ThicknessSoljun (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout5 (DD, D)Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact Finish ThicknessSoljari (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	50
Contact TypeSignalMounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish FinishSipin (1.27µm)Ingress Protection-Material Flammability RatingUL94 Yellow	Number of Rows	3
Mounting TypePanel MountFlange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish ThicknessSolpin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	5 (DD, D)
Flange FeatureHousing/Shell (Unthreaded)TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish ThicknessSolµin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolder CupFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 Yellow	Mounting Type	Panel Mount
Features-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder Cup
Contact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	-
Contact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Yellow Chromate Plated Cadmium
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	50µin (1.27µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
•		Report errors?

DDMMY50PA101 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DDMMY50PA101 Payment Methods



DDMMY50PA101 Shipping Methods



If you have any question about DDMMY50PA101, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com