



DE1A1B-L2-4.5V Information

Heisener.com

Part Number DE1A1B-L2-4.5V

Manufacturer Panasonic Electric Works

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 8A 4.5V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DE1A1B-L2-4.5V Specifications

Manufacturer Part Number DE1A1B-L2-4.5V Manufacturer Panasonic Electric Works Category Relays Power Relays, Over 2 Amps Package - Series DE Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 44.5mA Coil Voltage 4.5VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 3.15 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesDERelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current44.5mACoil Voltage4.5VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)3.15 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	DE1A1B-L2-4.5V
Package-SeriesDERelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current44.5mACoil Voltage4.5VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)3.15 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Panasonic Electric Works
Package-SeriesDERelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current44.5mACoil Voltage4.5VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)3.15 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesDERelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current44.5mACoil Voltage4.5VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)3.15 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current44.5mACoil Voltage4.5VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)8ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)3.15 VDCTurn Off Voltage (Min)-Operate Time10msRelease Time5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil Type Latching, Dual Coil Coil Current 44.5mA Coil Voltage 4.5VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 3.15 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Series	DE
Coil Current Coil Voltage 4.5VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 3.15 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 4.5VDC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 3.15 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Dual Coil
Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 8A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 3.15 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Current	44.5mA
Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 3.15 VDC Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole Termination Style	Coil Voltage	4.5VDC
Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 3.15 VDC Turn Off Voltage (Min) - Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	DPST-NO/NC (1 Form A and B)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole Termination Style 3.15 VDC - Turn Off Voltage (Min) - Turn Off Voltage	Contact Rating (Current)	8A
Turn Off Voltage (Min) Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 30VDC - Max
Operate Time 10ms Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	3.15 VDC
Release Time 5ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	10ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

DE1A1B-L2-4.5V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DE1A1B-L2-4.5V Payment Methods



















DE1A1B-L2-4.5V Shipping Methods













If you have any question about DE1A1B-L2-4.5V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com