

# DEMM9PHA101

quest a Quote

## **DEMM9PHA101 Information**

Contraction for the second for the s	Part Number	DEMM9PHA101
	Manufacturer	ITT Cannon, LLC
	Category	Connectors, Interconnects D-Sub Connectors
	Description	CONN DSUB PLUG 9POS PNL MNT SLDR
	Package	-
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **DEMM9PHA101 Specifications**

Manufacturer Part Number DEMM9PHA101   Manufacturer ITT Cannon, LLC   Category Connectors, Interconnects   D-Sub Connectors D-Sub Connectors   Package -   Series MIL-DTL-24308, D*MM   Connector Style D-Sub   Connector Type Plug, Male Pins   Number of Positions 9   Number of Rows 2   Stell Size, Connector Layout 1 (DE, E)   Contact Type Signal   Mounting Type Panel Mount, Through Hole   Flange Feature Solder   Features Solder   Contact Finish Steel, Yellow Chromate Plated Cadmium   Contact Finish Thickness Solpin (1.27µm)   Ingress Protection UL94 V-0		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesMIL-DTL-24308, D*MMConnector StyleD-Sub ConnectorConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Schalt Size, Connector Layout1(DE, E)Contact TypeSignalMounting TypeSolderFlange FeatureSolderFlange FeaturesSolderShell Material, FinishStel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish ThicknessSoly (1.27µm)Ingress Protection9Material Flammability RatingUBy V-0	Manufacturer Part Number	DEMM9PHA101
PackageD-Sub ConnectorsPackage-SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFeatures-Shell Material, FinishStel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Manufacturer	ITT Cannon, LLC
Package-SeriesML-DTL-24308,D*MMConnector StyleD-SubConnector TypePlag, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector LayoutIDE, E, EContact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFeatures-Shell Material, FinishStel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingU54 Vel	Category	Connectors, Interconnects
SeriesMIL-DTL-24308, D*MMConnector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish ThicknessSupin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypePlug, Male PinsNumber of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact Finish ThicknessSoljuin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Series	MIL-DTL-24308, D*MM
Number of Positions9Number of Rows2Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishStel, Yellow Chromate Plated CadmiumContact FinishGoldIngress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Number of Rows1 (DE, E)Shell Size, Connector LayoutSignalContact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishStel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish ThicknessSoljuni (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Plug, Male Pins
Shell Size, Connector Layout1 (DE, E)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	9
Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypePanel Mount, Through HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	1 (DE, E)
Flange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeatures-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Panel Mount, Through Hole
Features-Features-Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 Yellow	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Yellow Chromate Plated CadmiumContact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Features	-
Contact Finish Thickness50µin (1.27µm)Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Yellow Chromate Plated Cadmium
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	50μin (1.27μm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
1		Report errors?

#### **DEMM9PHA101 Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **DEMM9PHA101** Payment Methods



## **DEMM9PHA101** Shipping Methods



If you have any question about DEMM9PHA101, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com