

Heisener.com

# DPD090020-P7/RN-TC

#### DPD090020-P7/RN-TC Information

Part Number DPD090020-P7/RN-TC

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC WALL MOUNT ADAPTER 9V 2W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









### DPD090020-P7/RN-TC Specifications

Manufacturer Part Number         DPD090020-P7/RN-TC           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         9V           Current - Output (Max)         200mA           Power (Watts)         1.8W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         9V           Current - Output (Max)         200mA           Power (Watts)         1.8W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Manufacturer Part Number	DPD090020-P7/RN-TC
Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         9V           Current - Output (Max)         200mA           Power (Watts)         1.8W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Manufacturer	CUI Inc.
Package         -           Series         -           Region Utilized         North America           Form         Wall Mount           Input Type         Fixed Blade           Voltage - Input         120VAC           Voltage - Output         9V           Current - Output (Max)         200mA           Power (Watts)         1.8W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Category	Power Supplies - External/Internal (Off-Board)
Series-Region UtilizedNorth AmericaFormWall MountInput TypeFixed BladeVoltage - Input120VACVoltage - Output9VCurrent - Output (Max)200mAPower (Watts)1.8WNo Load Power Consumption-PolarizationNegative CenterApplicationsITE (Commercial)Efficiency-Operating Temperature-Output ConnectorBarrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mmSize / Dimension2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Wall Mount Input Type Fixed Blade Voltage - Input 120VAC Voltage - Output 9V Current - Output (Max) 200mA Power (Watts) 1.8W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Package	-
Form Wall Mount Input Type Fixed Blade  Voltage - Input 120VAC  Voltage - Output 9V  Current - Output (Max) 200mA  Power (Watts) 1.8W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Series	-
Input Type Fixed Blade  Voltage - Input 120VAC  Voltage - Output 9V  Current - Output (Max) 200mA  Power (Watts) 1.8W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Region Utilized	North America
Voltage - Input  120VAC  Voltage - Output  9V  Current - Output (Max)  200mA  Power (Watts)  1.8W  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  120VAC  9V  120VAC  9V  1.8W  1.8W  1.8W  No Load Power Consumption  - Overating Temperature  Output Connector  Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Form	Wall Mount
Voltage - Output (Max) 200mA  Power (Watts) 1.8W  No Load Power Consumption -  Polarization Negative Center Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension 2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Input Type	Fixed Blade
Current - Output (Max)  200mA  Power (Watts)  1.8W  No Load Power Consumption  - Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  - Operating Temperature  Output Connector  Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Voltage - Input	120VAC
Power (Watts)  1.8W  No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Voltage - Output	9V
No Load Power Consumption  Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Current - Output (Max)	200mA
Polarization Negative Center  Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Power (Watts)	1.8W
Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm Size / Dimension 2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Polarization	Negative Center
Operating Temperature  Output Connector  Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm  Size / Dimension  2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Applications	ITE (Commercial)
Output Connector         Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm           Size / Dimension         2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Efficiency	-
Size / Dimension 2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)	Operating Temperature	-
	Output Connector	Barrel Plug R/A, 1.3mm I.D. x 3.5mm O.D. x 8.5mm
Report errors?	Size / Dimension	2.63" L x 1.65" W x 1.17" H (66.7mm x 41.8mm x 29.6mm)
		Report errors?

#### DPD090020-P7/RN-TC Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### DPD090020-P7/RN-TC Payment Methods



















## DPD090020-P7/RN-TC Shipping Methods













If you have any question about DPD090020-P7/RN-TC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com