

DPFF16D33J-F

DPFF16D33J-F Information

www.neisener.com	 DPFF16D33J-F Cornell Dubilier Electronics (CDE) Capacitors Film Capacitors CAP FILM 3300PF 5% 1.6KVDC RAD Radial For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



DPFF16D33J-F Specifications

Manufacturer Part NumberDPFF16D33J-FManufacturerCornell Dubilier Electronics (CDE)CategoryCapacitorsPackageFlin CapacitorsSeriesRadialCapacitance3300pFCapacitance±5%Voltage Rating - AC500VVoltage Rating - DC1600V (1.6kV)Dielectric Material-Spreise-Operating Temperature-Package / CaseRadialSize / Dimension1.299" L x 0.551" W (33.00mm x 14.00mm)Fight - Seated (Max)0.51" (14.00mm)Lead SpacingO.720" (18.30mm)		
CategoryCapacitorsPackageRadialPackageRadialSeriesDPFFCapacitance3300pFTolerance±5%Voltage Rating - AC500VVoltage Rating - DC1600V (1.6kV)Dielectric Material-Operating Temperature-55°C ~ 105°CMounting TypeThrough HoleSize / Dimension1.299" L x 0.551" W (33.00mm x 14.00mm)Height - Seated (Max)0.551" (14.00mm)FerminationPC Pins	Manufacturer Part Number	DPFF16D33J-F
Film CapacitorsPackageRadialSeriesDPFFCapacitance3300pFTolerance±5%Voltage Rating - AC500VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRadialSize / Dimension1.299° L x 0.551" W (33.00mm x 14.00mm)Height - Seated (Max)OC Pins	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadialSeriesDPFFCapacitance3300pFTolerance±5%Voltage Rating - AC500VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRadialSize / Dimension1.299° L x 0.551° W (33.00mm x 14.00mm)Height - Seated (Max)OSTin (14.00mm)FerminationPC Pins	Category	Capacitors
Series DPFF Capacitance 3300pF Tolerance ±5% Voltage Rating - AC 500V Voltage Rating - DC 1600V (1.6kV) Dielectric Material Polyproplene (PP), Metallized Dielectric Material - Operating Temperature - Mounting Type Stor 205°C Package / Case Radial Size / Dimension 1.299" L x 0.551" W (33.00mm x 14.00mm) Height - Seated (Max) 0.551" (14.00mm)		Film Capacitors
Capacitance3300pFTolerance±5%Voltage Rating - AC500VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.299" L x 0.551" W (33.00mm x 14.00mm)Height - Seated (Max)9C Pins	Package	Radial
Tolerance±5%Voltage Rating - AC500VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.299" L x 0.551" W (33.00mm x 14.00mm)Height - Seated (Max)0.551" (14.00mm)PerminationPC Pins	Series	DPFF
Voltage Rating - AC500VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.299" L x 0.551" W (33.00mm x 14.00mm)Height - Seated (Max)0.551" (14.00mm)PerminationPC Pins	Capacitance	3300pF
Voltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.299" L x 0.551" W (33.00mm x 14.00mm)Height - Seated (Max)0.551" (14.00mm)PerminationPC Pins	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.299" L x 0.551" W (33.00mm x 14.00mm)Height - Seated (Max)0.551" (14.00mm)PerminationPC Pins	Voltage Rating - AC	500V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.299" L x 0.551" W (33.00mm x 14.00mm)Height - Seated (Max)0.551" (14.00mm)TerminationPC Pins	Voltage Rating - DC	1600V (1.6kV)
Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.299" L x 0.551" W (33.00mm x 14.00mm)Height - Seated (Max)0.551" (14.00mm)TerminationPC Pins	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension1.299" L x 0.551" W (33.00mm x 14.00mm)Height - Seated (Max)0.551" (14.00mm)TerminationPC Pins	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.299" L x 0.551" W (33.00mm x 14.00mm)Height - Seated (Max)0.551" (14.00mm)TerminationPC Pins	Operating Temperature	-55°C ~ 105°C
Size / Dimension 1.299" L x 0.551" W (33.00mm x 14.00mm) Height - Seated (Max) 0.551" (14.00mm) Termination PC Pins	Mounting Type	Through Hole
Height - Seated (Max)0.551" (14.00mm)TerminationPC Pins	Package / Case	Radial
Termination PC Pins	Size / Dimension	1.299" L x 0.551" W (33.00mm x 14.00mm)
	Height - Seated (Max)	0.551" (14.00mm)
Lead Spacing 0.720" (18.30mm)	Termination	PC Pins
· ·	Lead Spacing	0.720" (18.30mm)
Applications High Pulse, DV/DT	Applications	High Pulse, DV/DT
Features -	Features	-
Report errors		Report errors?

DPFF16D33J-F Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DPFF16D33J-F Payment Methods



DPFF16D33J-F Shipping Methods



If you have any question about DPFF16D33J-F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com