



DT100PW360D Information



For Reference Only

Part Number DT100PW360D

Manufacturer TDK-Lambda Americas Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 36V 100W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DT100PW360D Specifications

Manufacturer Part Number DT100PW360D Manufacturer TDK-Lambda Americas Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series DT100-D Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 36V Current - Output (Max) 2.78A Power (Watts) 100W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.70" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)		
CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesDT100-DRegion UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output36VCurrent - Output (Max)2.78APower (Watts)100WNo Load Power Consumption-Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 60°COutput ConnectorPower DIN, 4 PinSize / Dimension6.70" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Manufacturer Part Number	DT100PW360D
Package - Series DT100-D Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 36V Current - Output (Max) 2.78A Power (Watts) 100W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.70" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Manufacturer	TDK-Lambda Americas Inc.
Package - Series DT100-D Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 36V Current - Output (Max) 2.78A Power (Watts) 100W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.70" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series DT100-D Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 36V Current - Output (Max) 2.78A Power (Watts) 100W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.70" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 36V Current - Output (Max) 2.78A Power (Watts) 100W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.70" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Package	-
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 36V Current - Output (Max) 2.78A Power (Watts) 100W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.70" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Series	DT100-D
Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 36V Current - Output (Max) 2.78A Power (Watts) 100W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.70" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 36V Current - Output (Max) 2.78A Power (Watts) 100W No Load Power Consumption-Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorPower DIN, 4 PinSize / Dimension $6.70^{\circ}\text{L x } 3.35^{\circ}\text{W x } 1.73^{\circ}\text{H } (170.0 \text{mm x } 85.0 \text{mm x } 44.0 \text{mm})$	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 2.78A Power (Watts) 100W No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 36V 2.78A 100W ITE (Commercial) Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin 6.70" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 2.78A Power (Watts) 100W No Load Power Consumption - Polarization Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 2.78A 100W Level VI Commercial 0°C ~ 60°C Output Connector Power DIN, 4 Pin 6.70" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $100W$ No Load Power Consumption-Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature 0° C ~ 60° COutput ConnectorPower DIN, 4 PinSize / Dimension 6.70 " L x 3.35 " W x 1.73 " H (170.0 mm x 85.0 mm x 44.0 mm)	Voltage - Output	36V
No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 60°C Output Connector Power DIN, 4 Pin Size / Dimension 6.70" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Current - Output (Max)	2.78A
Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $6.70^{\circ}\text{L} \times 3.35^{\circ} \text{W} \times 1.73^{\circ} \text{H} (170.0 \text{mm} \times 85.0 \text{mm} \times 44.0 \text{mm})$	Power (Watts)	100W
Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0° C $\sim 60^{\circ}$ C Output Connector Power DIN, 4 Pin Size / Dimension 6.70° L x 3.35° W x 1.73° H (170.0mm x 85.0mm x 44.0mm)	No Load Power Consumption	-
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $6.70^{\circ}\text{L x } 3.35^{\circ}\text{W x } 1.73^{\circ}\text{H } (170.0\text{mm x } 85.0\text{mm x } 44.0\text{mm})$	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $6.70^{\circ}\text{L x } 3.35^{\circ}\text{W x } 1.73^{\circ}\text{H } (170.0\text{mm x } 85.0\text{mm x } 44.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Power DIN, 4 Pin Size / Dimension 6.70" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Efficiency	Level VI
Size / Dimension 6.70" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	Power DIN, 4 Pin
Report errors?	Size / Dimension	6.70" L x 3.35" W x 1.73" H (170.0mm x 85.0mm x 44.0mm)
		Report errors?

DT100PW360D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DT100PW360D Payment Methods





















DT100PW360D Shipping Methods













If you have any question about DT100PW360D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com