

# DTR050150-P13/RN

### DTR050150-P13/RN Information

Heisener.com

Part Number DTR050150-P13/RN

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 5V 8W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## DTR050150-P13/RN Specifications

Manufacturer Part Number         DTR050150-P13/RN           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           Package         -           Series         -           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         120V AC           Voltage - Output         5V           Current - Output (Max)         1.5A           Power (Watts)         7.5W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm           Size / Dimension         4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         -           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         120VAC           Voltage - Output         5V           Current - Output (Max)         1.5A           Power (Watts)         7.5W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm           Size / Dimension         4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Manufacturer Part Number	DTR050150-P13/RN
Package         -           Series         -           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         120VAC           Voltage - Output         5V           Current - Output (Max)         1.5A           Power (Watts)         7.5W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm           Size / Dimension         4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Manufacturer	CUI Inc.
Package         -           Series         -           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         120VAC           Voltage - Output         5V           Current - Output (Max)         1.5A           Power (Watts)         7.5W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm           Size / Dimension         4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         -           Region Utilized         North America           Form         Desktop (Class II)           Input Type         Cord           Voltage - Input         120VAC           Voltage - Output         5V           Current - Output (Max)         1.5A           Power (Watts)         7.5W           No Load Power Consumption         -           Polarization         Negative Center           Applications         ITE (Commercial)           Efficiency         -           Operating Temperature         -           Output Connector         Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm           Size / Dimension         4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 120VAC Voltage - Output 5V Current - Output (Max) 1.5A Power (Watts) 7.5W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Package	-
Form Desktop (Class II) Input Type Cord Voltage - Input 120VAC Voltage - Output 5V Current - Output (Max) 1.5A Power (Watts) 7.5W No Load Power Consumption - Polarization Negative Center Applications ITE (Commercial) Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Series	-
Input Type Cord  Voltage - Input 120VAC  Voltage - Output 5V  Current - Output (Max) 1.5A  Power (Watts) 7.5W  No Load Power Consumption -  Polarization Negative Center  Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm  Size / Dimension 4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Region Utilized	North America
Voltage - Input  Voltage - Output  5V  Current - Output (Max)  1.5A  Power (Watts)  No Load Power Consumption  - Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm  4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Form	Desktop (Class II)
Voltage - Output (Max) 1.5A  Power (Watts) 7.5W  No Load Power Consumption -  Polarization Negative Center Applications ITE (Commercial)  Efficiency -  Operating Temperature -  Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm  Size / Dimension 4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Input Type	Cord
Current - Output (Max)  1.5A  Power (Watts)  7.5W  No Load Power Consumption  - Polarization  Negative Center  Applications  ITE (Commercial)  Efficiency  - Operating Temperature  Output Connector  Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm  Size / Dimension  4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Voltage - Input	120VAC
Power (Watts)  7.5W  No Load Power Consumption  Polarization  Negative Center  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm  4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Voltage - Output	5V
No Load Power Consumption  Polarization  Negative Center  ITE (Commercial)  Efficiency  Operating Temperature  Output Connector  Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm  4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Current - Output (Max)	1.5A
Polarization Negative Center  Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Power (Watts)	7.5W
Applications ITE (Commercial)  Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	No Load Power Consumption	-
Efficiency - Operating Temperature - Output Connector Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm Size / Dimension 4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Polarization	Negative Center
Operating Temperature  Output Connector  Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm  4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Applications	ITE (Commercial)
Output Connector         Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm           Size / Dimension         4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Efficiency	-
Size / Dimension 4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)	Operating Temperature	-
	Output Connector	Barrel Plug R/A, 1.7mm I.D. x 4.0mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.74" L x 3.05" W x 2.24" H (120.5mm x 77.5mm x 57.0mm)
		Report errors?

#### DTR050150-P13/RN Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### DTR050150-P13/RN Payment Methods

































If you have any question about DTR050150-P13/RN, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com