

DWM-24-56-G-D-250 Information

Heisener.com

For Reference Only

Part Number DWM-24-56-G-D-250

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Board Spacers, Stackers

(Board to Board)

Description .050" BOARD SPACERS

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









DWM-24-56-G-D-250 Specifications

Manufacturer Part NumberDWM-24-56-G-D-250ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Board Spacers, Stackers (Board to Board)Package-SeriesFlex Stack, DWMNumber of Positions48Pitch0.050" (1.27mm)Number of Rows2Row Spacing0.100" (2.54mm)Length - Overall0.625" (15.88mm)Length - Post (Mating)0.255" (6.48mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolderContact Finish - Post (Mating)Gold		
Category Connectors, Interconnects Rectangular Connectors - Board Spacers, Stackers (Board to Board) Package - Series Flex Stack, DWM Number of Positions 48 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.625" (15.88mm) Length - Post (Mating) 0.255" (6.48mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder	Manufacturer Part Number	DWM-24-56-G-D-250
Rectangular Connectors - Board Spacers, Stackers (Board to Board) Package - Series Flex Stack, DWM Number of Positions 48 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.625" (15.88mm) Length - Post (Mating) 0.255" (6.48mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder	Manufacturer	Samtec Inc.
Package - Series Flex Stack, DWM Number of Positions 48 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.625" (15.88mm) Length - Post (Mating) 0.255" (6.48mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder	Category	Connectors, Interconnects
Series Flex Stack, DWM Number of Positions 48 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.625" (15.88mm) Length - Post (Mating) 0.255" (6.48mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder		Rectangular Connectors - Board Spacers, Stackers (Board to Board)
Number of Positions 48 Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.625" (15.88mm) Length - Post (Mating) 0.255" (6.48mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder	Package	-
Pitch 0.050" (1.27mm) Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.625" (15.88mm) Length - Post (Mating) 0.255" (6.48mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder	Series	Flex Stack, DWM
Number of Rows 2 Row Spacing 0.100" (2.54mm) Length - Overall 0.625" (15.88mm) Length - Post (Mating) 0.255" (6.48mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder	Number of Positions	48
Row Spacing 0.100" (2.54mm) Length - Overall 0.625" (15.88mm) Length - Post (Mating) 0.255" (6.48mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder	Pitch	0.050" (1.27mm)
Length - Overall 0.625" (15.88mm) Length - Post (Mating) 0.255" (6.48mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder	Number of Rows	2
Length - Post (Mating) 0.255" (6.48mm) Length - Stack Height 0.250" (6.35mm) Length - Tail 0.120" (3.05mm) Mounting Type Through Hole Termination Solder	Row Spacing	0.100" (2.54mm)
Length - Stack Height0.250" (6.35mm)Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolder	Length - Overall	0.625" (15.88mm)
Length - Tail0.120" (3.05mm)Mounting TypeThrough HoleTerminationSolder	Length - Post (Mating)	0.255" (6.48mm)
Mounting Type Through Hole Termination Solder	Length - Stack Height	0.250" (6.35mm)
Termination Solder	Length - Tail	0.120" (3.05mm)
	Mounting Type	Through Hole
Contact Finish - Post (Mating) Gold	Termination	Solder
	Contact Finish - Post (Mating)	Gold
Contact Finish Thickness - Post (Mating) 10µin (0.25µm)	Contact Finish Thickness - Post (Mating)	10μin (0.25μm)
Color Black	Color	Black
Report errors?		Report errors?

DWM-24-56-G-D-250 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

DWM-24-56-G-D-250 Payment Methods





















DWM-24-56-G-D-250 Shipping Methods













If you have any question about DWM-24-56-G-D-250, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com