



E-L6207D013TR Information



For Reference Only

Part Number E-L6207D013TR

Manufacturer STMicroelectronics

Category Integrated Circuits (ICs)

PMIC - Full, Half-Bridge Drivers

Description IC BRIDGE DRIVER PAR 24SOIC

Package 24-SOIC (0.295", 7.50mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









E-L6207D013TR Specifications

Manufacturer Part Number E-L6207D013TR Manufacturer STMicroelectronics Category Integrated Circuits (ICs) PACKAGE 24-SOIC (0.295", 7.50mm Width) Series - Output Configuration Half Bridge (4) Applications DC Motors, Stepper Motors, Voltage Regulators Interface Logic Load Type Inductive Technology DMOS Rds On (Typ) 300 mOhm Current - Output / Channel 2.8A Current - Peak Output 5.6A Voltage - Supply 8 V ~ 52 V Voltage - Load 8 V ~ 52 V Operating Temperature -25°C ~ 125°C (TJ) Features Bootstrap Circuit Fault Protection Current Limiting, Over Temperature, UVLO Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package 24-SOI		
Category Integrated Circuits (ICs) PMIC - Full, Half-Bridge Drivers Package 24-SOIC (0.295", 7.50mm Width) Series - Output Configuration Half Bridge (4) Applications DC Motors, Stepper Motors, Voltage Regulators Interface Logic Load Type Inductive Technology DMOS Rds On (Typ) 300 mOhm Current - Output / Channel 2.8A Current - Peak Output 5.6A Voltage - Supply 8 V ~ 52 V Voltage - Load 8 V ~ 52 V Operating Temperature -25°C ~ 125°C (TJ) Features Bootstrap Circuit Fault Protection Current Limiting, Over Temperature, UVLO Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package 24-SOIC	Manufacturer Part Number	E-L6207D013TR
PACKAGE PACKAGE 24-SOIC (0.295", 7.50mm Width) Series - Output Configuration Half Bridge (4) Applications DC Motors, Stepper Motors, Voltage Regulators Interface Logic Load Type Inductive Technology DMOS Rds On (Typ) 300 mOhm Current - Output / Channel Current - Peak Output Voltage - Supply Voltage - Load 8 V ~ 52 V Voltage - Load Operating Temperature -25°C ~ 125°C (TJ) Features Bootstrap Circuit Fault Protection Mounting Type Surface Mount Valed - Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package 24-SOI	Manufacturer	STMicroelectronics
Package 24-SOIC (0.295", 7.50mm Width) Series - Output Configuration Half Bridge (4) Applications DC Motors, Stepper Motors, Voltage Regulators Interface Logic Load Type Inductive Technology DMOS Rds On (Typ) 300 mOhm Current - Output / Channel 2.8A Current - Peak Output 5.6A Voltage - Supply 8 V ~ 52 V Voltage - Load 8 V ~ 52 V Operating Temperature -25°C ~ 125°C (TJ) Features Bootstrap Circuit Fault Protection Current Limiting, Over Temperature, UVLO Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package 24-SO	Category	Integrated Circuits (ICs)
Series - Output Configuration Half Bridge (4) Applications DC Motors, Stepper Motors, Voltage Regulators Interface Logic Load Type Inductive Technology DMOS Rds On (Typ) 300 mOhm Current - Output / Channel 2.8A Current - Peak Output 5.6A Voltage - Supply 8 V ~ 52 V Voltage - Load 8 V ~ 52 V Operating Temperature -25°C ~ 125°C (TJ) Features Bootstrap Circuit Fault Protection Current Limiting, Over Temperature, UVLO Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package 24-SO		PMIC - Full, Half-Bridge Drivers
Output ConfigurationHalf Bridge (4)ApplicationsDC Motors, Stepper Motors, Voltage RegulatorsInterfaceLogicLoad TypeInductiveTechnologyDMOSRds On (Typ)300 mOhmCurrent - Output / Channel2.8ACurrent - Peak Output5.6AVoltage - Supply8 V ~ 52 VVoltage - Load8 V ~ 52 VOperating Temperature-25°C ~ 125°C (TJ)FeaturesBootstrap CircuitFault ProtectionCurrent Limiting, Over Temperature, UVLOMounting TypeSurface MountPackage / Case24-SOIC (0.295", 7.50mm Width)Supplier Device Package24-SO	Package	24-SOIC (0.295", 7.50mm Width)
Applications DC Motors, Stepper Motors, Voltage Regulators Interface Logic Load Type Inductive Technology DMOS Rds On (Typ) 300 mOhm Current - Output / Channel 2.8A Current - Peak Output 5.6A Voltage - Supply 8 V ~ 52 V Voltage - Load 8 V ~ 52 V Operating Temperature -25°C ~ 125°C (TJ) Features Bootstrap Circuit Fault Protection Current Limiting, Over Temperature, UVLO Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package	Series	-
Interface Logic Load Type Inductive Technology DMOS Rds On (Typ) 300 mOhm Current - Output / Channel 2.8A Current - Peak Output 5.6A Voltage - Supply 8 V ~ 52 V Voltage - Load 8 V ~ 52 V Operating Temperature -25°C ~ 125°C (TJ) Features Bootstrap Circuit Fault Protection Current Limiting, Over Temperature, UVLO Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package	Output Configuration	Half Bridge (4)
Load TypeInductiveTechnologyDMOSRds On (Typ)300 mOhmCurrent - Output / Channel2.8ACurrent - Peak Output5.6AVoltage - Supply8 V ~ 52 VVoltage - Load8 V ~ 52 VOperating Temperature-25°C ~ 125°C (TJ)FeaturesBootstrap CircuitFault ProtectionCurrent Limiting, Over Temperature, UVLOMounting TypeSurface MountPackage / Case24-SOIC (0.295", 7.50mm Width)Supplier Device Package24-SO	Applications	DC Motors, Stepper Motors, Voltage Regulators
Technology Rds On (Typ) 300 mOhm Current - Output / Channel 2.8A Current - Peak Output 5.6A Voltage - Supply 8 V ~ 52 V Voltage - Load 8 V ~ 52 V Operating Temperature -25°C ~ 125°C (TJ) Features Bootstrap Circuit Fault Protection Current Limiting, Over Temperature, UVLO Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package	Interface	Logic
Rds On (Typ) 300 mOhm Current - Output / Channel 2.8A Current - Peak Output 5.6A Voltage - Supply 8 V ~ 52 V Voltage - Load 8 V ~ 52 V Operating Temperature -25°C ~ 125°C (TJ) Features Bootstrap Circuit Fault Protection Current Limiting, Over Temperature, UVLO Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package	Load Type	Inductive
Current - Output / Channel Current - Peak Output 5.6A Voltage - Supply Voltage - Load 8 V ~ 52 V Operating Temperature -25°C ~ 125°C (TJ) Features Bootstrap Circuit Fault Protection Current Limiting, Over Temperature, UVLO Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package	Technology	DMOS
Current - Peak Output 5.6A Voltage - Supply 8 V ~ 52 V Voltage - Load 8 V ~ 52 V Operating Temperature -25°C ~ 125°C (TJ) Features Bootstrap Circuit Fault Protection Current Limiting, Over Temperature, UVLO Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package	Rds On (Typ)	300 mOhm
Voltage - Supply $8 V \sim 52 V$ Voltage - Load $8 V \sim 52 V$ Operating Temperature $-25^{\circ}\text{C} \sim 125^{\circ}\text{C}$ (TJ) Features Bootstrap Circuit Fault Protection Current Limiting, Over Temperature, UVLO Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package 24-SO	Current - Output / Channel	2.8A
Voltage - Load $8 \text{ V} \sim 52 \text{ V}$ Operating Temperature $-25^{\circ}\text{C} \sim 125^{\circ}\text{C}$ (TJ) Features Bootstrap Circuit Fault Protection Current Limiting, Over Temperature, UVLO Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package 24-SO	Current - Peak Output	5.6A
Operating Temperature -25°C ~ 125°C (TJ) Features Bootstrap Circuit Fault Protection Current Limiting, Over Temperature, UVLO Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package 24-SO	Voltage - Supply	8 V ~ 52 V
Features Bootstrap Circuit Fault Protection Current Limiting, Over Temperature, UVLO Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package 24-SO	Voltage - Load	8 V ~ 52 V
Fault Protection Current Limiting, Over Temperature, UVLO Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package 24-SO	Operating Temperature	-25°C ~ 125°C (TJ)
Mounting Type Surface Mount Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package 24-SO	Features	Bootstrap Circuit
Package / Case 24-SOIC (0.295", 7.50mm Width) Supplier Device Package 24-SO	Fault Protection	Current Limiting, Over Temperature, UVLO
Supplier Device Package 24-SO	Mounting Type	Surface Mount
	Package / Case	24-SOIC (0.295", 7.50mm Width)
Report errors?	Supplier Device Package	24-SO
		Report errors?

E-L6207D013TR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

E-L6207D013TR Payment Methods



















E-L6207D013TR Shipping Methods













If you have any question about E-L6207D013TR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com