

Heisener.com

E37F421CPN392ME92M

E37F421CPN392ME92M Information

Part Number E37F421CPN392ME92M

Manufacturer United Chemi-Con

Category Capacitors

Aluminum Electrolytic Capacitors

CAP ALUM 3900UF 20% 420V SCREW **Description**

Radial, Can - Screw Terminals **Package**

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









E37F421CPN392ME92M Specifications

Manufacturer Part Number E37F421CPN392ME92M Manufacturer United Chemi-Con Category Capacitors Package Radial, Can - Screw Terminals Series U37F Capacitance 3900µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 24 mOhm @ 120Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 13.2A @ 120Hz Ripple Current - High Frequency 23.124A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 3.661" (93.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	*	
Category Capacitors Package Radial, Can - Screw Terminals Series U37F Capacitance 3900μF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 24 mOhm @ 120Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13.2A @ 120Hz Ripple Current - High Frequency 23.124A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 3.661" (93.00mm) Surface Mount Land Size - Mounting Type Chassis Mount	Manufacturer Part Number	E37F421CPN392ME92M
Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series U37F Capacitance 3900µF Tolerance ±20% Voltage - Rated ESR (Equivalent Series Resistance) 24 mOhm @ 120Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency 13.2A @ 120Hz Ripple Current - High Frequency 1.252" (31.80mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount	Manufacturer	United Chemi-Con
PackageRadial, Can - Screw TerminalsSeriesU37FCapacitance3900μFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)24 mOhm @ 120HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency13.2A @ 120HzRipple Current - High Frequency23.124A @ 10kHzImpedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis Mount	Category	Capacitors
Series U37F Capacitance 3900µF Tolerance ±20% Voltage - Rated 420V ESR (Equivalent Series Resistance) 24 mOhm @ 120Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13.2A @ 120Hz Ripple Current - High Frequency 23.124A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 3.661" (93.00mm) Surface Mount Land Size - Mounting Type Chassis Mount		Aluminum Electrolytic Capacitors
Capacitance3900µFTolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)24 mOhm @ 120HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency13.2A @ 120HzRipple Current - High Frequency23.124A @ 10kHzImpedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis Mount	Package	Radial, Can - Screw Terminals
Tolerance±20%Voltage - Rated420VESR (Equivalent Series Resistance)24 mOhm @ 120HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency13.2A @ 120HzRipple Current - High Frequency23.124A @ 10kHzImpedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis Mount	Series	U37F
Voltage - Rated420VESR (Equivalent Series Resistance)24 mOhm @ 120HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency13.2A @ 120HzRipple Current - High Frequency23.124A @ 10kHzImpedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis Mount	Capacitance	3900μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 13.2A @ 120Hz Ripple Current - High Frequency 23.124A @ 10kHz Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 24 mOhm @ 120Hz 24 mOhm @ 120Hz 24 mOhm @ 120Hz 25000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C General Purpose 13.2A @ 120Hz 23.124A @ 10kHz 1.252" (31.80mm) 3.000" Dia (76.20mm) 3.000" Dia (76.20mm) 4.61" (93.00mm) 5.000 Height - Seated (Max) 6.000 Height - Seat	Tolerance	±20%
Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13.2A @ 120Hz Ripple Current - High Frequency 23.124A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Chassis Mount	Voltage - Rated	420V
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 23.124A @ 120Hz Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) Surface Mount Land Size Mounting Type -40°C ~ 85°C General Purpose 13.2A @ 120Hz 23.124A @ 10kHz 1.252" (31.80mm) 1.252" (31.80mm) 3.000" Dia (76.20mm) Chassis Mount	ESR (Equivalent Series Resistance)	24 mOhm @ 120Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 13.2A @ 120Hz Ripple Current - High Frequency 23.124A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 3.661" (93.00mm) Surface Mount Land Size - Mounting Type Chassis Mount	Lifetime @ Temp.	5000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 23.124A @ 10kHz Impedance - Lead Spacing 1.252" (31.80mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) 3.661" (93.00mm) Surface Mount Land Size Mounting Type Chassis Mount	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 23.124A @ 10kHz Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) Surface Mount Land Size Mounting Type 13.2A @ 120Hz 23.124A @ 10kHz - Chassis Mount	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 1.252" (31.80mm) Size / Dimension 3.000" Dia (76.20mm) Height - Seated (Max) Surface Mount Land Size Mounting Type 23.124A @ 10kHz - Chassis Mount	Applications	General Purpose
Impedance-Lead Spacing1.252" (31.80mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis Mount	Ripple Current - Low Frequency	13.2A @ 120Hz
Lead Spacing1.252" (31.80mm)Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis Mount	Ripple Current - High Frequency	23.124A @ 10kHz
Size / Dimension3.000" Dia (76.20mm)Height - Seated (Max)3.661" (93.00mm)Surface Mount Land Size-Mounting TypeChassis Mount	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type 3.661" (93.00mm) - Chassis Mount	Lead Spacing	1.252" (31.80mm)
Surface Mount Land Size - Mounting Type Chassis Mount	Size / Dimension	3.000" Dia (76.20mm)
Mounting Type Chassis Mount	Height - Seated (Max)	3.661" (93.00mm)
C 31	Surface Mount Land Size	-
Package / Case Radial, Can - Screw Terminals	Mounting Type	Chassis Mount
	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

E37F421CPN392ME92M Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

E37F421CPN392ME92M Payment Methods



















E37F421CPN392ME92M Shipping Methods













If you have any question about E37F421CPN392ME92M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com