



### **EBA35DCMI-S288 Information**

Heisener.com

Part Number EBA35DCMI-S288

Manufacturer Sullins Connector Solutions
Category Connectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

**Description** CONN EDGE DUAL FMALE 70POS 0.125

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **EBA35DCMI-S288 Specifications**

Manufacturer Part Number         EBA35DCMI-S288           Manufacturer         Sullins Connector Solutions           Category         Connectors, Interconnects           Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         35           Number of Positions         70           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.125" (3.18mm)           Features         Card Extender           Mounting Type         Board Edge, Straddle Mount           Termination         Wire Wrap           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Hairpin Bellows           Color         -           Flange Feature         Top Mount Opening, Threaded Insert, 4-40           Operating Temperature         -65°C ~ 125°C	DB/135DCM1-5250 Specifications	
Category       Connectors, Interconnects         Package       -         Series       -         Card Type       Non Specified - Dual Edge         Gender       Female         Number of Positions/Bay/Row       35         Number of Positions       70         Card Thickness       0.062" (1.57mm)         Number of Rows       2         Pitch       0.125" (3.18mm)         Features       Card Extender         Mounting Type       Board Edge, Straddle Mount         Termination       Wire Wrap         Contact Material       Phosphor Bronze         Contact Finish       Gold         Contact Type       Hairpin Bellows         Color       -         Flange Feature       Top Mount Opening, Threaded Insert, 4-40         Operating Temperature       -65°C ~ 125°C	Manufacturer Part Number	EBA35DCMI-S288
Package Series Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 35 Number of Positions Number of Positions  Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.125" (3.18mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Wire Wrap Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10μin (0.25μm) Contact Type Hairpin Bellows Color Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature - 65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package         -           Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         35           Number of Positions         70           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.125" (3.18mm)           Features         Card Extender           Mounting Type         Board Edge, Straddle Mount           Termination         Wire Wrap           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10µin (0.25µm)           Contact Type         Hairpin Bellows           Color         -           Flange Feature         Top Mount Opening, Threaded Insert, 4-40           Operating Temperature         -65°C ~ 125°C	Category	Connectors, Interconnects
Series         -           Card Type         Non Specified - Dual Edge           Gender         Female           Number of Positions/Bay/Row         35           Number of Positions         70           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.125" (3.18mm)           Features         Card Extender           Mounting Type         Board Edge, Straddle Mount           Termination         Wire Wrap           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Hairpin Bellows           Color         -           Flange Feature         Top Mount Opening, Threaded Insert, 4-40           Operating Temperature         -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row35Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Package	-
Gender         Female           Number of Positions/Bay/Row         35           Number of Positions         70           Card Thickness         0.062" (1.57mm)           Number of Rows         2           Pitch         0.125" (3.18mm)           Features         Card Extender           Mounting Type         Board Edge, Straddle Mount           Termination         Wire Wrap           Contact Material         Phosphor Bronze           Contact Finish         Gold           Contact Finish Thickness         10μin (0.25μm)           Contact Type         Hairpin Bellows           Color         -           Flange Feature         Top Mount Opening, Threaded Insert, 4-40           Operating Temperature         -65°C ~ 125°C	Series	-
Number of Positions/Bay/Row  Number of Positions  70  Card Thickness  0.062" (1.57mm)  Number of Rows  2  Pitch  0.125" (3.18mm)  Features  Card Extender  Mounting Type  Board Edge, Straddle Mount  Wire Wrap  Contact Material  Phosphor Bronze  Contact Finish  Gold  Contact Finish Thickness  10µin (0.25µm)  Contact Type  Hairpin Bellows  Color  Flange Feature  Top Mount Opening, Threaded Insert, 4-40  Operating Temperature  35  40  40  40  40  40  40  40  40  40  4	Card Type	Non Specified - Dual Edge
Number of Positions70Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.125" (3.18mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	35
Number of Rows2Pitch0.125" (3.18mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions	70
Pitch0.125" (3.18mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationWire WrapContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Pitch	0.125" (3.18mm)
Termination Wire Wrap  Contact Material Phosphor Bronze  Contact Finish Gold  Contact Finish Thickness $10\mu$ in $(0.25\mu$ m)  Contact Type Hairpin Bellows  Color -  Flange Feature Top Mount Opening, Threaded Insert, 4-40  Operating Temperature $-65^{\circ}$ C $\sim 125^{\circ}$ C	Features	Card Extender
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeHairpin BellowsColor-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Mounting Type	Board Edge, Straddle Mount
Contact Finish  Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type  Hairpin Bellows  Color  Flange Feature  Top Mount Opening, Threaded Insert, 4-40  Operating Temperature  -65°C ~ 125°C	Termination	Wire Wrap
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Hairpin Bellows Color - Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact Type Hairpin Bellows  Color -  Flange Feature Top Mount Opening, Threaded Insert, 4-40  Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color-Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Type	Hairpin Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	-
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

#### **EBA35DCMI-S288 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **EBA35DCMI-S288 Payment Methods**





















## **EBA35DCMI-S288 Shipping Methods**













If you have any question about EBA35DCMI-S288, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com