



### **ECD-G0ER909 Information**

Part Number ECD-G0ER909

Manufacturer Panasonic Electronic Components

**Category** Capacitors

**Ceramic Capacitors** 

**Description** CAP CER 0.9PF 25V C0G/NP0 0402

**Package** 0402 (1005 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ECD-G0ER909 Specifications**

Manufacturer Part Number         ECD-GOER909           Manufacturer         Panasonic Electronic Components           Category         Capacitors           Package         0402 (1005 Metric)           Series         ECD           Capacitance         0.9pF           Tolerance         ±0.075pF           Voltage - Rated         25V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.022" (0.55mm)           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         0402 (1005 Metric)           Series         ECD           Capacitance         0.9pF           Tolerance         ±0.075pF           Voltage - Rated         25V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.022" (0.55mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	ECD-G0ER909
Package         0402 (1005 Metric)           Series         ECD           Capacitance         0.9pF           Tolerance         ±0.075pF           Voltage - Rated         25V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.022" (0.55mm)           Lead Spacing         -           Lead Style         -	Manufacturer	Panasonic Electronic Components
Package         0402 (1005 Metric)           Series         ECD           Capacitance         0.9pF           Tolerance         ±0.075pF           Voltage - Rated         25V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.022" (0.55mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         ECD           Capacitance         0.9pF           Tolerance         ±0.075pF           Voltage - Rated         25V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.022" (0.55mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         0.9pF           Tolerance         ±0.075pF           Voltage - Rated         25V           Temperature Coefficient         COG, NPO           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.022" (0.55mm)           Lead Spacing         -           Lead Style         -	Package	0402 (1005 Metric)
Tolerance         ±0.075pF           Voltage - Rated         25V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         High Q, Low Loss           Ratings         -           Applications         RF, Microwave, High Frequency           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.022" (0.55mm)           Lead Spacing         -           Lead Style         -	Series	ECD
Voltage - Rated  25V  Temperature Coefficient  COG, NPO  Operating Temperature  -55°C ~ 125°C  Features  High Q, Low Loss  Ratings  - Applications  RF, Microwave, High Frequency  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  0402 (1005 Metric)  Size / Dimension  0.039" L x 0.020" W (1.00mm x 0.50mm)  Height - Seated (Max)  - Thickness (Max)  0.022" (0.55mm)  Lead Spacing  - Lead Style	Capacitance	0.9pF
Temperature Coefficient  Operating Temperature  -55°C ~ 125°C  Features  High Q, Low Loss  Ratings  -  Applications  RF, Microwave, High Frequency  Failure Rate  -  Mounting Type  Surface Mount, MLCC  Package / Case  0402 (1005 Metric)  Size / Dimension  0.039" L x 0.020" W (1.00mm x 0.50mm)  Height - Seated (Max)  Thickness (Max)  1. Cad Spacing  -  Lead Style  -  COG, NP0  -55°C ~ 125°C  High Q, Low Loss  Article Q, Low Loss  High Q, Low Loss  -  High Q, Low Loss  -  High Q, Low Loss  -  1. Can Company  -  1. Can Compa	Tolerance	±0.075pF
Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsRF, Microwave, High FrequencyFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0402 (1005 Metric)Size / Dimension0.039" L x 0.020" W (1.00mm x 0.50mm)Height - Seated (Max)-Thickness (Max)0.022" (0.55mm)Lead Spacing-Lead Style-	Voltage - Rated	25V
Features High Q, Low Loss  Ratings - Applications RF, Microwave, High Frequency  Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 0402 (1005 Metric)  Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm)  Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm)  Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - RF, Microwave, High Frequency Failure Rate - Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style - Surface Mount, MLCC	Operating Temperature	-55°C ~ 125°C
Applications RF, Microwave, High Frequency Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Features	High Q, Low Loss
Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0402 (1005 Metric)           Size / Dimension         0.039" L x 0.020" W (1.00mm x 0.50mm)           Height - Seated (Max)         -           Thickness (Max)         0.022" (0.55mm)           Lead Spacing         -           Lead Style         -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0402 (1005 Metric) Size / Dimension 0.039" L x 0.020" W (1.00mm x 0.50mm) Height - Seated (Max) - Thickness (Max) 0.022" (0.55mm) Lead Spacing - Lead Style -	Applications	RF, Microwave, High Frequency
Package / Case       0402 (1005 Metric)         Size / Dimension       0.039" L x 0.020" W (1.00mm x 0.50mm)         Height - Seated (Max)       -         Thickness (Max)       0.022" (0.55mm)         Lead Spacing       -         Lead Style       -	Failure Rate	-
Size / Dimension       0.039" L x 0.020" W (1.00mm x 0.50mm)         Height - Seated (Max)       -         Thickness (Max)       0.022" (0.55mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	0402 (1005 Metric)
Thickness (Max) 0.022" (0.55mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.039" L x 0.020" W (1.00mm x 0.50mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.022" (0.55mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

### **ECD-G0ER909 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ECD-G0ER909 Payment Methods**



















### **ECD-G0ER909 Shipping Methods**













If you have any question about ECD-G0ER909, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com