

ECSR200

ECSR200 Information

10					
(2)	н	612	еп	er	
147					

Part Number	ECSR200	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	UL CLASS RK-5 TIME DELAY	
Package	Cylindrical, Blade Terminals	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECSR200 Specifications

Anufacturer Eaton Category Eicotrical Protection Beckage Cylindrical, Blade Terminals Package Cylindrical, Blade Terminals Series Cylindrical, Blade Terminals Series ECSR Fuse Type Cartridge Current Rating 200A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Pactures - Class RS5 Approvals CE, CSA, ULL Operating Temperature - Breaking Capacity @ Rated Voltage 200KA Mounting Type Holder Package / Case Sitorical, Blade Terminals		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesECSRFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassKS5Operating Temperature200AAOperating TemperatureCE, CSA, ULOperating Type-Mounting TypeHolderPackage / CaseSjindrical, Blade TerminalsSize / Dimension1.610" Diax 9.630" L (40.89mm x 244.60mm)	Manufacturer Part Number	ECSR200
Bit of the section o	Manufacturer	Eaton
PackageCylindrical, Blade TerminalsSeriesECSRFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Type-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.610" Dia x 9.630" L (40.89mm x 244.60mm)	Category	Circuit Protection
SeriesECSRFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsElectroactOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.610" Dia x 9.630" L (40.89mm x 244.60mm)		Electrical, Specialty Fuses
FunctionControlFuse TypeCartridgeCurrent Rating200AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.610" Dia x 9.630" L (40.89mm x 244.60mm)	Package	Cylindrical, Blade Terminals
Current Rating200AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature200kABreaking Capacity @ Rated VoltageBolderMounting TypeHolderPackage / CaseCylindrical, Blade TeminalsSize / Dimension1.610" Dia x 9.630" L (40.89mm x 244.60mm)	Series	ECSR
Voltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature200kABreaking Capacity @ Rated VoltageHolderMounting TypeHolderPackage / CaseSilminialsSize / Dimension1.610" Dia x 9.630" L (40.89mm x 244.60mm)	Fuse Type	Cartridge
Voltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.610" Dia x 9.630" L (40.89mm x 244.60mm)	Current Rating	200A
Response TimeSlowApplicationsElectrical, IndustrialApplications-Features-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.610" Dia x 9.630" L (40.89mm x 244.60mm)	Voltage Rating - AC	600V
ApplicationsElectrical, IndustrialApplications-Features-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.610" Dia x 9.630" L (40.89mm x 244.60mm)	Voltage Rating - DC	-
Features-Features-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.610" Dia x 9.630" L (40.89mm x 244.60mm)	Response Time	Slow
ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.610" Dia x 9.630" L (40.89mm x 244.60mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.610" Dia x 9.630" L (40.89mm x 244.60mm)	Features	-
A-Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.610" Dia x 9.630" L (40.89mm x 244.60mm)	Class	RK5
Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.610" Dia x 9.630" L (40.89mm x 244.60mm)	Approvals	CE, CSA, UL
Mounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.610" Dia x 9.630" L (40.89mm x 244.60mm)	Operating Temperature	-
Package / CaseCylindrical, Blade TerminalsSize / Dimension1.610" Dia x 9.630" L (40.89mm x 244.60mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.610" Dia x 9.630" L (40.89mm x 244.60mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	1.610" Dia x 9.630" L (40.89mm x 244.60mm)
		Report errors?

ECSR200 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECSR200 Payment Methods Image: Imag

If you have any question about ECSR200, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com