

# ECW-H8202HL

### **ECW-H8202HL Information**

Heisener.com	 ECW-H8202HL Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 2000PF 3% 800VDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **ECW-H8202HL Specifications**

Manufacturer Part NumberECW-H8202HLManufacturerPanasonic Electronic ComponentsCategoryCapacitorsPackageRadialPackageRadialSeriesECW-H(L)Capacitance2000pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolyproplene (PP), MetallizedOperating Temperature-40°C ~ 110°CMounting TypeThrough HoleSize / Dimension0.70°T Lx 0.236°W (18.00mm x 6.00mm)Height - Seated (Max)0.571" (14.50mm)Lead Spacing691" (15.00mm)Applications1641 Frequency, Switching		
CategoryCapacitorsPackageRadialPackageRadialSeriesECW-H(L)Capacitance2000pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolyproplene (PP), MetallizedDoperating Temperature-Operating Temperature-40°C ~ 110°CMounting TypeThrough HoleSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.571" (14.50mm)Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Manufacturer Part Number	ECW-H8202HL
Film CapacitorsPackageRadialSeriesECW-H(L)Capacitance2000pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-40°C ~110°CMounting TypeThrough HoleSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.571" (14.50mm)Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECW-H(L)Capacitance2000pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-Mounting TypeHough HolePackage / CaseRadialSize / Dimension0.70° L x 0.236° W (18.00mm x 6.00mm)Height - Seated (Max)0.571" (14.50mm)IreminationDS1" (15.00mm)ApplicationsSige Frequency, Switching	Category	Capacitors
SeriesECW-H(L)Capacitance2000pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolyproplene (PP), MetallizedDielectric Material-Operating Temperature-Operating TemperatureRadiaPackage / CaseRadiaSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.571" (14.50mm)TerminationDC PinsApplications0.591" (15.00mm)ApplicationsHigh Frequency, Switching		Film Capacitors
Capacitance2000pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolyproplene (PP), MetallizedDielectric Material-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.571" (14.50mm)TerminationDC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Package	Radial
Tolerance±3%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.570" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)DS1" (14.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Series	ECW-H(L)
Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.571" (14.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Capacitance	2000pF
Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.571" (14.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Tolerance	±3%
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.571" (14.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.571" (14.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Voltage Rating - DC	800V
Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.571" (14.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.571" (14.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.571" (14.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Operating Temperature	-40°C ~ 110°C
Size / Dimension0.709" L x 0.236" W (18.00mm x 6.00mm)Height - Seated (Max)0.571" (14.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Mounting Type	Through Hole
Height - Seated (Max)0.571" (14.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Package / Case	Radial
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Size / Dimension	0.709" L x 0.236" W (18.00mm x 6.00mm)
Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Height - Seated (Max)	0.571" (14.50mm)
Applications High Frequency, Switching	Termination	PC Pins
	Lead Spacing	0.591" (15.00mm)
Easterna	Applications	High Frequency, Switching
reatures -	Features	-
Report errors		Report errors?

#### **ECW-H8202HL Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# **ECW-H8202HL Payment Methods**



## **ECW-H8202HL Shipping Methods**



If you have any question about ECW-H8202HL, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com