

EEC44DRTS-S13

est a Quote

EEC44DRTS-S13 Information

Part Number	EEC44DRTS-S13	
Manufacturer	Sullins Connector Solutions	
Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	ģ
Description Package	CONN EDGE DUAL FMALE 88POS 0.100	- 2
	-	-
	For the pricing/inventory/lead time, please contact	
	us Walation https://www.haiaanaa	
For Reference Only	E-mail: salesdept@heisener.com	R
	Manufacturer Category Description	Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors Description CONN EDGE DUAL FMALE 88POS 0.100 Package - For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



EEC44DRTS-S13 Specifications

ManufacturerSullins Connector SolutionsCadegoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesGoader Edge, Straddle MountTerminationSolderContact FinishSolderContact Finish Thickness100µin (2.54µm)Contact TypeGual Edge, Straddle MountContact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact TypeHul BellowsContact TypeSull SolderContact TypeSull Solder <th></th> <th></th>		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions/Bay/Row88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialNologen BronzeContact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact TypeHul BellowsContact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsContact TypeSide MountColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18µm) DiaOperating Temperature-65°C ~ 125°C	Manufacturer Part Number	EEC44DRTS-S13
Card Edge Connectors - Edgeboard Connectors Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 44 Number of Positions 88 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Mounting Type Board Edge, Straddle Mount Contact Material Phosphor Bronze Contact Finish Tin Contact Finish Thickness 100µin (2.54µm) Contact Type Full Bellows Contact Type Full Bellows Color Bue Flange Feature Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialPhosphor BronzeContact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsContact TypeSide Mount Opening, Unthreaded, 0.125" (3.18mm) Dia 65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions/Bay/Row88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact FinishTinContact Finish Thickness100µin (2.54µm)Contact Finish ThicknessBuleContact TypeSulderContact TypeSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaContart Finsh ThickneseSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaContact TypeSide Mount Opening, Unth		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialNosphor BronzeContact Finish Thickness100µin (2.54µm)Contact TypeHolle BlowsContact TypeSiderContact TypeSiderContact TypeSide SiderContact TypeSide SiderContact TypeSide SiderContact TypeSide SiderContact TypeSide SiderContact TypeSiderContact TypeSide SiderContact TypeSide SiderContact TypeSide SiderContact TypeSide SiderContact TypeSiderContact TypeSider Sider	Package	-
GenderFemaleNumber of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialYhosphor BronzeContact FinishTinContact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row44Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions88Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	44
Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	88
Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	Card Extender
Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Board Edge, Straddle Mount
Contact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Tin
ColorBlueFlange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	100µin (2.54µm)
Flange FeatureSide Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Blue
	Flange Feature	Side Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

EEC44DRTS-S13 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

EEC44DRTS-S13 Payment Methods



EEC44DRTS-S13 Shipping Methods



If you have any question about EEC44DRTS-S13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com