



## **EEU-FC1H391S Information**

www.heisener.com

For Reference Only

Part Number EEU-FC1H391S

Manufacturer Panasonic Electronic Components

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 390UF 20% 50V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **EEU-FC1H391S Specifications**

Manufacturer Part Number       EEU-FC1H391S         Manufacturer       Panasonic Electronic Components         Category       Capacitors         Aluminum Electrolytic Capacitors         Package       Radial, Can         Series       Automotive, AEC-Q200, FC         Capacitance       390μF         Tolerance       ±20%         Voltage - Rated       50V         ESR (Equivalent Series Resistance)       -         Lifetime @ Temp.       5000 Hrs @ 105°C         Operating Temperature       -55°C ~ 105°C         Polarization       Polar         Applications       Automotive         Ripple Current - Low Frequency       1.208A @ 120Hz         Ripple Current - High Frequency       1.61A @ 100kHz         Impedance       80 mOhms         Lead Spacing       0.295" (7.50mm)         Size / Dimension       0.630" Dia (16.00mm)         Height - Seated (Max)       0.591" (15.00mm)         Surface Mount Land Size       -         Mounting Type       Through Hole         Package / Case       Radial, Can		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series Automotive, AEC-Q200, FC Capacitance 390µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Incla @ 100kHz Ripple Current - High Frequency Lead Spacing 0.295" (7.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can	Manufacturer Part Number	EEU-FC1H391S
Package Radial, Can Series Automotive, AEC-Q200, FC Capacitance 390µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 1.208A @ 120Hz Ripple Current - High Frequency 1.61A @ 100kHz Impedance 80 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.591" (15.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Panasonic Electronic Components
PackageRadial, CanSeriesAutomotive, AEC-Q200, FCCapacitance390μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency1.208A @ 120HzRipple Current - High Frequency1.61A @ 100kHzImpedance80 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.591" (15.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Category	Capacitors
Series         Automotive, AEC-Q200, FC           Capacitance         390µF           Tolerance         ±20%           Voltage - Rated         50V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         5000 Hrs @ 105°C           Operating Temperature         -55°C ~ 105°C           Polarization         Polar           Applications         Automotive           Ripple Current - Low Frequency         1.208A @ 120Hz           Ripple Current - High Frequency         1.61A @ 100kHz           Impedance         80 mOhms           Lead Spacing         0.295" (7.50mm)           Size / Dimension         0.630" Dia (16.00mm)           Height - Seated (Max)         0.591" (15.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can		Aluminum Electrolytic Capacitors
Capacitance       390μF         Tolerance       ±20%         Voltage - Rated       50V         ESR (Equivalent Series Resistance)       -         Lifetime @ Temp.       5000 Hrs @ 105°C         Operating Temperature       -55°C ~ 105°C         Polarization       Polar         Applications       Automotive         Ripple Current - Low Frequency       1.208A @ 120Hz         Ripple Current - High Frequency       1.61A @ 100kHz         Impedance       80 mOhms         Lead Spacing       0.295" (7.50mm)         Size / Dimension       0.630" Dia (16.00mm)         Height - Seated (Max)       0.591" (15.00mm)         Surface Mount Land Size       -         Mounting Type       Through Hole         Package / Case       Radial, Can	Package	Radial, Can
Tolerance ±20%  Voltage - Rated 50V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 5000 Hrs @ 105°C  Operating Temperature -55°C ~ 105°C  Polarization Polar  Applications Automotive  Ripple Current - Low Frequency 1.208A @ 120Hz  Ripple Current - High Frequency 1.61A @ 100kHz  Impedance 80 mOhms  Lead Spacing 0.295" (7.50mm)  Size / Dimension 0.630" Dia (16.00mm)  Height - Seated (Max) 0.591" (15.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Series	Automotive, AEC-Q200, FC
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  5000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  Automotive  Ripple Current - Low Frequency  Ripple Current - High Frequency  1.208A @ 120Hz  Impedance  80 mOhms  Lead Spacing  0.295" (7.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Polor  -  5000 Hrs @ 105°C  -  6000 Hrs	Capacitance	390μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  5000 Hrs @ 105°C  Operating Temperature  -55°C ~ 105°C  Polar  Applications  Automotive  Ripple Current - Low Frequency  1.208A @ 120Hz  Ripple Current - High Frequency  1.61A @ 100kHz  Impedance  80 mOhms  Lead Spacing  0.295" (7.50mm)  Size / Dimension  0.630" Dia (16.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -55°C ~ 105°C  Polarization  Applications  Automotive  Ripple Current - Low Frequency  Ripple Current - High Frequency  1.208A @ 120Hz  Rippedance  80 mOhms  Lead Spacing  0.295" (7.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  5000 Hrs @ 105°C  -55°C ~ 105°C  -105°C  Automotive  1.208A @ 120Hz  1.208A @ 120Hz  1.61A @ 100kHz  1.	Voltage - Rated	50V
Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 1.208A @ 120Hz Ripple Current - High Frequency 1.61A @ 100kHz Impedance 80 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.591" (15.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Applications Automotive Ripple Current - Low Frequency 1.208A @ 120Hz Ripple Current - High Frequency 1.61A @ 100kHz Impedance 80 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.591" (15.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	5000 Hrs @ 105°C
Applications Ripple Current - Low Frequency 1.208A @ 120Hz Ripple Current - High Frequency 1.61A @ 100kHz Impedance 80 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.591" (15.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  1.61A @ 100kHz  Impedance  80 mOhms  Lead Spacing  0.295" (7.50mm)  Size / Dimension  0.630" Dia (16.00mm)  Height - Seated (Max)  0.591" (15.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance 80 mOhms Lead Spacing 0.295" (7.50mm) Size / Dimension 0.630" Dia (16.00mm) Height - Seated (Max) 0.591" (15.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	Automotive
Impedance80 mOhmsLead Spacing0.295" (7.50mm)Size / Dimension0.630" Dia (16.00mm)Height - Seated (Max)0.591" (15.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	1.208A @ 120Hz
Lead Spacing 0.295" (7.50mm)  Size / Dimension 0.630" Dia (16.00mm)  Height - Seated (Max) 0.591" (15.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Ripple Current - High Frequency	1.61A @ 100kHz
Size / Dimension 0.630" Dia (16.00mm)  Height - Seated (Max) 0.591" (15.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can	Impedance	80 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.630" Dia (16.00mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.591" (15.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
•		Report errors?

#### **EEU-FC1H391S Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **EEU-FC1H391S Payment Methods**



















### **EEU-FC1H391S Shipping Methods**













If you have any question about EEU-FC1H391S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com