

# EMC26DREH-S734

#### **EMC26DREH-S734** Information

Heisener.com	Part Number Manufacturer Category Description Package	EMC26DREH-S734 Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 52POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **EMC26DREH-S734 Specifications**

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions/Bay/Row0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish ThicknessGoldContact TypeGuld (0.76µm)Contact TypeFull BellowsContact TypeSolder Eyelet(s)Contact Finish ThicknessGoldContact TypeFull BellowsColorBueFlage FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaGoperating Temperature-65°C ~ 125°C			
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish ThicknessGoldContact Finish ThicknessSupin (0.76µm)Contact TypeFull BellowsContact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)Contact TypeGoldContact TypeSupin (0.76µm)Contact TypeSupin (0.76µm)Contact TypeGoldContact TypeSupin (0.76µm)ColorBlueFlange FeatureCop (0.0125" (3.18mm) DiaCoperating Temperature-50°C ~125°C	Manufacturer Part Number	EMC26DREH-S734	
AndCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Card Thickness0.031" (0.79mm)Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeFull BellowsColorBueFinage Feature- 56°C ~ 125°C	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Card Thickness0.031" (0.79mm)Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish ThicknessGoldContact Finish ThicknessGuldContact TypeFull BellowsContact TypeFull BellowsContact TypeGuldContact TypeGuldContact TypeGuldContact TypeGuldContact TypeFull BellowsContact TypeGuldContact TypeGuld <td>Category</td> <td>Connectors, Interconnects</td> <td></td>	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact FinishSolder Eyelet(s)Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColtact TypeSolder Sylet Syl		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-	
GenderFemaleNumber of Positions/Bay/Row26Number of Positions52Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact FinishGoldContact TypeFull BellowsColorBlueFlarge FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Series	-	
Number of Positions/Bay/Row26Number of Positions52Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBueFlarge FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge	
Number of Positions 52   Card Thickness 0.031" (0.79mm)   Number of Rows 2   Pitch 0.100" (2.54mm)   Features -   Mounting Type Panel Mount   Termination Solder Eyelet(s)   Contact Material Phosphor Bronze   Contact Finish Thickness Gold   Contact Type Full Bellows   Color Blue   Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia   Operating Temperature -65°C ~ 125°C	Gender	Female	
Card Thickness0.031" (0.79mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFull BellowsColorBueFlange Feature-Operating Temperature-	Number of Positions/Bay/Row	26	
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Positions	52	
Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.031" (0.79mm)	
Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Number of Rows	2	
Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)	
TerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Mounting Type	Panel Mount	
Contact FinishGoldContact Finish Thickness30μin (0.76μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Termination	Solder Eyelet(s)	
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze	
Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish	Gold	
ColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)	
Flange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Contact Type	Full Bellows	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Blue	
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia	
Report errors?	Operating Temperature	$-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	
			Report errors?

#### **EMC26DREH-S734 Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **EMC26DREH-S734 Payment Methods**



#### **EMC26DREH-S734 Shipping Methods**



If you have any question about EMC26DREH-S734, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com