



ESM030W-0700-32 Information

Heisener.com

Part Number ESM030W-0700-32 Manufacturer ERP Power, LLC

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CC AC/DC 21-32V 700MA

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESM030W-0700-32 Specifications

Manufacturer Part Number ESM030W-0700-32 Manufacturer ERP Power, LLC Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series ESM Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 700mA Power (Watts) 22W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)			
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series ESM Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 700mA Power (Watts) 22W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Manufacturer Part Number	ESM030W-0700-32	
Package - Series ESM Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 700mA Power (Watts) 22W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Manufacturer	ERP Power, LLC	
Package - Series ESM Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 700mA Power (Watts) 22W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series ESM Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 700mA Power (Watts) 22W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)		LED Drivers	
Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 700mA Power (Watts) 22W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Package	-	
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 700mA Power (Watts) 22W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Series	ESM	
Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 700mA Power (Watts) 22W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Туре	Constant Current	
Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 700mA Power (Watts) 22W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Topology	AC DC Converter	
Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 700mA Power (Watts) 22W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Number of Outputs	1	
Voltage - Output 21 ~ 32 V Current - Output (Max) 700mA Power (Watts) 22W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Voltage - Input (Min)	120V	
Current - Output (Max) 700mA Power (Watts) 22W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Voltage - Input (Max)	277V	
Power (Watts) 22W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 22W L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Voltage - Output	21 ~ 32 V	
Voltage - Isolation Dimming ELV, Triac OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension -200°C - 200°C + 200°C Wire Leads 4.20° L x 2.37° W x 0.99° H (106.7mm x 60.3mm x 25.2mm)	Current - Output (Max)	700mA	
Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Power (Watts)	22W	
Features OCP, OTP, SCP Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Voltage - Isolation	-	
Ratings IP64, IP20, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Dimming	ELV, Triac	
Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Features	OCP, OTP, SCP	
Efficiency 87% Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Ratings	IP64, IP20, NEMA 410	
Termination Style Wire Leads Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Operating Temperature	-30°C ~ 90°C	
Size / Dimension 4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	Efficiency	87%	
	Termination Style	Wire Leads	
Report errors?	Size / Dimension	4.20" L x 2.37" W x 0.99" H (106.7mm x 60.3mm x 25.2mm)	
			Report errors?

ESM030W-0700-32 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESM030W-0700-32 Payment Methods



















ESM030W-0700-32 Shipping Methods













If you have any question about ESM030W-0700-32, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com