

ESQ-112-34-S-S-LL

ESQ-112-34-S-S-LL Information

	Part Number Manufacturer		
Contraction of the second second	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	ELEVATED SOCKET STRIPS	
	Package	-	国際登場
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQ-112-34-S-S-LL Specifications

Manufacturer Part NumberESQ-112-34-S-LLManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesESQContact TypeElevated SocketContact TypeBoard to BoardNumber of Positions12Number of Positions Loaded1.010° (2.54mm)Number of Rows1.010° (2.54mm)Number of Rows1.010° (2.54mm)Number of Rows1.010° (2.54mm)StriegMick Pin SolderMounting TypeThrough HoleContact Finish - Mating0.100° (2.54mm)Contact Finish - Mating6.31StriegSolderStriegMick Pin SolderContact Finish - Mating6.31Contact Finish - MatingGold (0.76µm)Contact Finish Thickness - MatingGoldor (0.76µm)Isulation ColorBackIsulation Height0.35° (16.13mm)Contact Length - Post0.280° (7.11mm)Contact Length - Post0.280° (7.11mm)Contact Infinish Mating0.280° (7.11mm)Contact Infinish Mating0.280° (7.11mm)Contact Infinish Mating0.280° (7.11mm)Contact Length - Post0.280° (7.11mm)Contact Infinish Mating0.280° (7.11mm)Contact Infinish Mating0.280° (7.11mm)Contact Infinish Mating0.280° (7.11mm)Contact Length - Post0.280° (7.11mm)Contact Length - Post0.280° (7.11mm)Contac		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesESQConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions12Number of Positions LoadedAllNumber of Rows1Number of Rows1Number of Rows1Number of Rows1StyleSocketStyleMine GaleNumber of Rows1Strong TypeSocketStrong TypeSocketStro	Manufacturer Part Number	ESQ-112-34-S-S-LL
Package-SeriesESQConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions12Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypeOddContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.76µm)Solation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)Operating Temperature-55°C ~ 125°C	Manufacturer	Samtec Inc.
Package-SeriesESQConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions12Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypeOddContact Finish - MatingGoldContact Finish Thickness - MatingJoin (0.76µm)Insulation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post.55°C ~ 125°C	Category	Connectors, Interconnects
SeriesESQConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions12Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypeGoldContact Finish - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions12Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypeOuldContact Finish - MatingGoldContact Finish - Mating0.jun (0.76µm)Insulation ColorBlackInsulation Height0.280" (7.11mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact TypeForkedStyleBoard to BoardNumber of Positions12Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypeOutContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)Operating Temperature-55°C ~ 125°C	Series	ESQ
StyleBoard to BoardNumber of Positions12Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.635" (16.13mm)Operating Temperature-55°C ~ 125°C	Connector Type	Elevated Socket
Number of Positions 12 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Kinked Pin, Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Jouin (0.76µm) Insulation Height 0.635" (16.13mm) Contact Length - Post 0.280" (7.11mm)	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)Operating Temperature55°C ~ 125°C	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBiackInsulation ColorBiackInsulation Height0.635" (16.13mm)Contact Length - Post55°C ~ 125°C	Number of Positions	12
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating-Row Spacing - MatingThrough HoleMounting TypeKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.76µm)Insulation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)Operating Temperature-55°C ~ 125°C	Number of Rows	1
TerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	-
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)Operating Temperature-55°C ~ 125°C	Termination	Kinked Pin, Solder
Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height 0.635" (16.13mm) Contact Length - Post 0.280" (7.11mm) Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	30µin (0.76µm)
Contact Length - Post0.280" (7.11mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.635" (16.13mm)
	Contact Length - Post	0.280" (7.11mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

ESQ-112-34-S-S-LL Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQ-112-34-S-S-LL Payment Methods



If you have any question about ESQ-112-34-S-S-LL, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com