

ESW-130-13-T-D

ESW-130-13-T-D Information

	Part Number Manufacturer	ESW-130-13-T-D Samtec Inc.	
Contraction the State Investment of the State Investme	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	ELEVATED SOCKET STRIPS	3853644
	Package	-	同語後報
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESW-130-13-T-D Specifications

Manufacturer Part NumberESW-130-13-T-DManufacturerSamtec Inc.CategoryConnectors, InterconnectsPackage-Package-SeriesESWConnector TypeElevated SocketContact TypeForkedNumber of Positions60Number of Positions Loaded100° (2.54mm)Number of Rows2Row Spacing - MatingNol0° (2.54mm)Mounting TypeIntorg HoleMounting TypeSolderContact Finish - MatingSolderFastening TypeIntoFastening TypeSolderFastening TypeIntoSolder Finish - MatingSolderFastening TypeSolderFastening TypeSolderFastening TypeSolderFastening TypeSolderFastening TypeSolderFastening TypeSolderFastening TypeSolderFastening TypeSolderFastening TypeSolderFastening TypeSolderFormationSolderFormationSolderFormationSolderFormationSolderFormationSolderFormationSolderFormationSolderFormationSolderFormationSolderFormationSolderFormationSolderFormationSolderFormationSolderFormationSolderFormationSolder <th></th> <th></th>		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesESWConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions60Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - MatingSolderMounting TypeSolderFerninationSolderFerninationSolderFortact Finish - Mating-Contact Finish - Mating-Solder Einish - Solder	Manufacturer Part Number	ESW-130-13-T-D
Number of PositionsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesESWConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions60Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - MatingNinogh HoleMounting TypeThrough HoleFastening TypePush-PullContact Finish - Mating.Otact Finish - Mating.	Manufacturer	Samtec Inc.
Package-SeriesESWConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions60Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeThrough HoleFastening TypeSolderFastening TypeInsh-PullContact Finish - Mating-Contact Finish - Mating-	Category	Connectors, Interconnects
SeriesESWConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions60Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeThrough HoleFastening TypeSolderFastening TypeInsContact Finish - Mating.Contact Finish Thickness - Mating.		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions60Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating.Contact Finish Thickness - Mating.	Package	-
Contact TypeForkedStyleBoard to BoardNumber of Positions60Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeOlor (2.54mm)TerminationSolderFastening TypePush-PullContact Finish - Mating-Contact Finish Thickness - Mating-	Series	ESW
StyleBoard to BoardNumber of Positions60Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating.Yunter ServerSingerMounting TypeSolderSolderSolderSolderSolderSolder ServerSolderSolder Server<	Connector Type	Elevated Socket
Number of Positions60Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating-Contact Finish Thickness - Mating-	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-	Number of Positions	60
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-	Number of Positions Loaded	All
Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-	Row Spacing - Mating	0.100" (2.54mm)
Fastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-	Mounting Type	Through Hole
Contact Finish - MatingTinContact Finish Thickness - Mating-	Termination	Solder
Contact Finish Thickness - Mating -	Fastening Type	Push-Pull
	Contact Finish - Mating	Tin
Insulation Color Black	Contact Finish Thickness - Mating	-
	Insulation Color	Black
Insulation Height 0.435" (11.05mm)	Insulation Height	0.435" (11.05mm)
Contact Length - Post 0.290" (7.37mm)	Contact Length - Post	0.290" (7.37mm)
Operating Temperature $-55^{\circ}C \sim 105^{\circ}C$	Operating Temperature	-55°C ~ 105°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

ESW-130-13-T-D Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESW-130-13-T-D Payment Methods



If you have any question about ESW-130-13-T-D, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com