

F30J750 Information

(A) Heisener.com

Part Number F30J750 Manufacturer Ohmite Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 750 OHM 5% 30W

Package Radial, Flat Oval

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









F301750	Specifications
T 30J / 30	Specifications

Manufacturer Part NumberF301750ManufacturerOhmiteCategoryResistorsPackageRadial, Flat OvalSeriesStackohm? 250Resistance750 OhmsTolerance±5%Power (Watts)30WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension1.250" L x 1.000" W (31.75mm x 25.40mm)Height - Seated (Max)0.563" (14.29mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-Report errors?		
CategoryResistorsPackageRadial, Flat OvalSeriesStackohm? 250Resistance750 OhmsTolerance±5%Power (Watts)30WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension1.250" L x 1.000" W (31.75mm x 25.40mm)Height - Seated (Max)0.563" (14.29mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Manufacturer Part Number	F30J750
Chassis Mount Resistors Package Radial, Flat Oval Series Stackohm? 250 Resistance 750 Ohms Tolerance ±5% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 1.250" L x 1.000" W (31.75mm x 25.40mm) Height - Seated (Max) 0.563" (14.29mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate	Manufacturer	Ohmite
PackageRadial, Flat OvalSeriesStackohm? 250Resistance750 OhmsTolerance±5%Power (Watts)30WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension1.250" L x 1.000" W (31.75mm x 25.40mm)Height - Seated (Max)0.563" (14.29mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Category	Resistors
SeriesStackohm? 250Resistance750 OhmsTolerance±5%Power (Watts)30WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension1.250" L x 1.000" W (31.75mm x 25.40mm)Height - Seated (Max)0.563" (14.29mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-		Chassis Mount Resistors
Resistance750 OhmsTolerance±5%Power (Watts)30WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension1.250" L x 1.000" W (31.75mm x 25.40mm)Height - Seated (Max)0.563" (14.29mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Package	Radial, Flat Oval
Tolerance ±5% Power (Watts) 30W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 1.250" L x 1.000" W (31.75mm x 25.40mm) Height - Seated (Max) 0.563" (14.29mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Series	Stackohm? 250
Power (Watts) Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 1.250" L x 1.000" W (31.75mm x 25.40mm) Height - Seated (Max) Lead Style Package / Case Radial, Flat Oval Failure Rate -	Resistance	750 Ohms
Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 1.250" L x 1.000" W (31.75mm x 25.40mm) Height - Seated (Max) 0.563" (14.29mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Tolerance	±5%
Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 1.250" L x 1.000" W (31.75mm x 25.40mm) Height - Seated (Max) 0.563" (14.29mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Power (Watts)	30W
Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 1.250" L x 1.000" W (31.75mm x 25.40mm) Height - Seated (Max) 0.563" (14.29mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Composition	Wirewound
Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 1.250" L x 1.000" W (31.75mm x 25.40mm) Height - Seated (Max) 0.563" (14.29mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Temperature Coefficient	±260ppm/°C
Coating, Housing Type Vitreous Enamel Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 1.250" L x 1.000" W (31.75mm x 25.40mm) Height - Seated (Max) 0.563" (14.29mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Operating Temperature	-55°C ~ 350°C
Mounting Feature Flange Braces, Right Angle 1.250" L x 1.000" W (31.75mm x 25.40mm) Height - Seated (Max) Lead Style Package / Case Radial, Flat Oval Failure Rate Flange Braces, Right Angle 1.250" L x 1.000" W (31.75mm x 25.40mm) Solder Lugs Failure Rate	Features	-
Size / Dimension 1.250" L x 1.000" W (31.75mm x 25.40mm) Height - Seated (Max) 0.563" (14.29mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max) Lead Style Package / Case Radial, Flat Oval Failure Rate 0.563" (14.29mm) Solder Lugs Radial, Flat Oval -	Mounting Feature	Flange Braces, Right Angle
Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Size / Dimension	1.250" L x 1.000" W (31.75mm x 25.40mm)
Package / Case Radial, Flat Oval Failure Rate -	Height - Seated (Max)	0.563" (14.29mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Flat Oval
Report errors?	Failure Rate	-
		Report errors?

F30J750 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

F30J750 Payment Methods





















F30J750 Shipping Methods













If you have any question about F30J750, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com