

F5-24 Information



For Reference Only

Part Number F5-24

Manufacturer Triad Magnetics

Category Transformers
Power Transformers

Description XFRMR LAMINATED THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









F5-24 Specifications

Manufacturer Part Number F5-24 Manufacturer Triad Magnetics Category Transformers Power Transformers Power Transformers Series Quick Pack Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 24V Current - Output (Max) 500mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 12 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) 41.28mm Voltage - Isolation 2500VAC Weight 0.7 lb (317.51g)		
Category Transformers Package - Series Quick Pack Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 24V Current - Output (Max) 500mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 12 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) 41.28mm Voltage - Isolation 2500VAC Weight 0.7 lb (317.51g)	Manufacturer Part Number	F5-24
Power Transformers Package - Series Quick Pack Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 24V Current - Output (Max) 500mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 12 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) 41.28mm Voltage - Isolation 2500VAC Weight 0.7 lb (317.51g)	Manufacturer	Triad Magnetics
Package - Quick Pack Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 24V Current - Output (Max) 500mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 12 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) 41.28mm Voltage - Isolation 2500VAC Weight	Category	Transformers
Series Quick Pack Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 24V Current - Output (Max) 500mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 12 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) 41.28mm Voltage - Isolation 2500VAC Weight		Power Transformers
Type Laminated Core Voltage - Primary 115V Voltage - Secondary (Full Load) 24V Current - Output (Max) 500mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 12 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) 41.28mm Voltage - Isolation 2500VAC Weight	Package	-
Voltage - Primary Voltage - Secondary (Full Load) 24V Current - Output (Max) Primary Winding(s) Single Secondary Winding(s) Secondary Winding(s) Single Center Tap Yes Power - Max 12 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation 0.7 lb (317.51g)	Series	Quick Pack
Voltage - Secondary (Full Load) Current - Output (Max) 500mA Primary Winding(s) Single Secondary Winding(s) Single Center Tap Yes Power - Max 12 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation 0.7 lb (317.51g)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Secondary Winding(s) Single Center Tap Yes Power - Max Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) Voltage - Isolation Weight 500mA Single Yes Chassis Mount 12 VA Solder, Quick Connect - 0.187" (4.7mm) 71.42mm L x 34.93mm W 41.28mm 0.7 1b (317.51g)	Voltage - Primary	115V
Primary Winding(s) Secondary Winding(s) Single Center Tap Yes Power - Max 12 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) Voltage - Isolation 2500VAC Weight	Voltage - Secondary (Full Load)	24V
Secondary Winding(s) Center Tap Yes Power - Max 12 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) Voltage - Isolation 2500VAC Weight	Current - Output (Max)	500mA
Center Tap Yes Power - Max 12 VA Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) 41.28mm Voltage - Isolation 2500VAC Weight 0.7 lb (317.51g)	Primary Winding(s)	Single
Power - Max Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) 41.28mm Voltage - Isolation 2500VAC Weight 0.7 lb (317.51g)	Secondary Winding(s)	Single
Mounting Type Chassis Mount Termination Style Solder, Quick Connect - 0.187" (4.7mm) Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) 41.28mm Voltage - Isolation 2500VAC Weight 0.7 lb (317.51g)	Center Tap	Yes
Termination Style Solder, Quick Connect - 0.187" (4.7mm) Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) 41.28mm Voltage - Isolation 2500VAC Weight 0.7 lb (317.51g)	Power - Max	12 VA
Size / Dimension 71.42mm L x 34.93mm W Height - Seated (Max) 41.28mm Voltage - Isolation 2500VAC Weight 0.7 lb (317.51g)	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation Veight 41.28mm 2500VAC 0.7 lb (317.51g)	Termination Style	Solder, Quick Connect - 0.187" (4.7mm)
Voltage - Isolation 2500VAC Weight 0.7 lb (317.51g)	Size / Dimension	71.42mm L x 34.93mm W
Weight 0.7 lb (317.51g)	Height - Seated (Max)	41.28mm
	Voltage - Isolation	2500VAC
Report errors?	Weight	0.7 lb (317.51g)
		Report errors?

F5-24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

F5-24 Payment Methods



















F5-24 Shipping Methods













If you have any question about F5-24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com