

FA-118T 26.0000MF10Z-AJ5

FA-118T 26.0000MF10Z-AJ5 Information



Part Number	FA-118T 26.0000MF10Z-AJ5	
Manufacturer	EPSON	
Category	Crystals, Oscillators, Resonators Crystals	
Description	CRYSTAL 26.0000MHZ 8.0PF SMD	
Package	4-SMD, No Lead	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FA-118T 26.0000MF10Z-AJ5 Specifications

Manufacturer Part Number FA-118T 26.000MF10Z-AJ5 Manufacturer EPSON Category Crystals, Oscillators, Resonators Category Crystals Package 4.SMD, No Lead Series FA-118T Type MHz Crystal Frequency 26MHz Frequency Stability ±10ppm Frequency Tolerance ±10ppm Load Capacitance 8pF ESR (Equivalent Series Resistance) 200 Ohm Operating Mode Fundamental Operating Temperature 4-0°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm)			
Category Crystals, Oscillators, Resonators Crystals Package 4-SMD, No Lead Series FA-118T Type MHz Crystal Frequency 26MHz Frequency Stability ±10ppm Frequency Tolerance ±10ppm Load Capacitance 8pF Operating Mode Fundamental Operating Temperature 40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4.SMD, No Lead Siz / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.04" (0.35mm)	Manufacturer Part Number	FA-118T 26.0000MF10Z-AJ5	
CrystalsPackage4-SMD, No LeadSeriesFA-118TTypeMHz CrystalTypency26MHzFrequency Stability±10ppmFrequency Tolerance±10ppmLoad Capacitance8pFESR (Equivalent Series Resistance)200 OhmOperating Mode-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case-SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)Height - Seated (Max)0.014" (0.35mm)	Manufacturer	EPSON	
Package4-SMD, No LeadSeriesFA-118TTypeMHz CrystalTrequency26MHzFrequency Stability±10ppmFrequency Tolerance±10ppmLoad Capacitance8pFESR (Equivalent Series Resistance)200 OhmOperating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)Height - Seated (Max)0.014" (0.35mm)	Category	Crystals, Oscillators, Resonators	
SeriesFA-118TTypeMHz CrystalFrequency26MHzFrequency Stability±10pmFrequency Tolerance±10pmLoad Capacitance8pFSSR (Equivalent Series Resistance)200 OhmOperating ModeFundamentalOperating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case4.5MD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)Height - Seated (Max)0.014" (0.35mm)		Crystals	
TypeMHz CrystalFrequency26MHzFrequency Stability±10pmFrequency Tolerance±10pmLoad Capacitance8pFESR (Equivalent Serisstance)200 OhmOperating ModeFundamentalOperating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)Height - Seated (Max)0.014" (0.35mm)	Package	4-SMD, No Lead	
Frequency26MHzFrequency Stability±10ppmFrequency Tolerance±10ppmLoad Capacitance8pFESR (Equivalent Series Resistance)200 OhmOperating ModeFundamentalOperating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)Height - Seated (Max)0.014" (0.35mm)	Series	FA-118T	
Frequency Stability±10ppmFrequency Tolerance±10ppmLoad Capacitance8pFESR (Equivalent Series Resistance)200 OhmOperating ModeFundamentalOperating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case4.SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)Height - Seated (Max)0.014" (0.35mm)	Туре	MHz Crystal	
Frequency Tolerance±10pmLoad Capacitance8pFESR (Equivalent Series Resistance)200 OhmOperating ModeFundamentalOperating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)Height - Seated (Max)0.014" (0.35mm)	Frequency	26MHz	
Load Capacitance8pFESR (Equivalent Series Resistance)200 OhmOperating ModeFundamentalOperating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)Height - Seated (Max)0.014" (0.35mm)	Frequency Stability	±10ppm	
ESR (Equivalent Series Resistance)200 OhmOperating ModeFundamentalOperating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)Height - Seated (Max)0.014" (0.35mm)	Frequency Tolerance	±10ppm	
Operating ModeFundamentalOperating Temperature-40°C ~ 85°CRatings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)Height - Seated (Max)0.014" (0.35mm)	Load Capacitance	8pF	
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.014" (0.35mm)	ESR (Equivalent Series Resistance)	200 Ohm	
Ratings-Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)Height - Seated (Max)0.014" (0.35mm)	Operating Mode	Fundamental	
Mounting TypeSurface MountPackage / Case4-SMD, No LeadSize / Dimension0.063" L x 0.047" W (1.60mm x 1.20mm)Height - Seated (Max)0.014" (0.35mm)	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$	
Package / Case 4-SMD, No Lead Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.014" (0.35mm)	Ratings	-	
Size / Dimension 0.063" L x 0.047" W (1.60mm x 1.20mm) Height - Seated (Max) 0.014" (0.35mm)	Mounting Type	Surface Mount	
Height - Seated (Max) 0.014" (0.35mm)	Package / Case	4-SMD, No Lead	
	Size / Dimension	0.063" L x 0.047" W (1.60mm x 1.20mm)	
Report errors?	Height - Seated (Max)	0.014" (0.35mm)	
			Report errors?

FA-118T 26.0000MF10Z-AJ5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

FA-118T 26.0000MF10Z-AJ5 Payment Methods



If you have any question about FA-118T 26.0000MF10Z-AJ5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com