



FCB-205-0119M Information



For Reference Only

Part Number FCB-205-0119M

Manufacturer TE Connectivity Aerospace, Defense and Marine

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 5A 28V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FCB-205-0119M Specifications

| Manufacturer Part Number Manufacturer TE Connectivity Aerospace, Defense and Marine Relays Power Relays, Over 2 Amps Package Series Military, MIL-R-83536/1, FCB, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage (Max) 18 VDC |
|--|
| Category Relays Power Relays, Over 2 Amps Package - Series Military, MIL-R-83536/1, FCB, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC |
| Package Packag |
| Package - Series Military, MIL-R-83536/1, FCB, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC |
| Series Military, MIL-R-83536/1, FCB, CII Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC |
| Relay Type General Purpose Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC |
| Coil Type Non Latching Coil Current - Coil Voltage 28VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC |
| Coil Current - Coil Voltage 28VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC |
| Coil Voltage 28VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC |
| Contact Form DPDT (2 Form C) Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC |
| Contact Rating (Current) 5A Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC |
| Switching Voltage 115VAC, 28VDC - Max Turn On Voltage (Max) 18 VDC |
| Turn On Voltage (Max) 18 VDC |
| - |
| |
| Turn Off Voltage (Min) 1.5 VDC |
| Operate Time 5ms |
| Release Time 5ms |
| Features Sealed - Hermetically |
| Mounting Type Through Hole |
| Termination Style PC Pin |
| Report errors |

FCB-205-0119M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FCB-205-0119M Payment Methods





















FCB-205-0119M Shipping Methods













If you have any question about FCB-205-0119M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com