

### FP88-130 Information

Heisener.com

Part Number FP88-130

Manufacturer Triad Magnetics
Category Transformers

**Power Transformers** 

**Description** PC MOUNT POWER TRANSFORMER

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# FP88-130 Specifications

For Reference Only

Manufacturer Part Number  Manufacturer  Category  Triad Magnetics  Transformers  Power Transformers  Package  - Series  FP  Type  Laminated Core  Voltage - Primary  Voltage - Secondary (Full Load)  Parallel 44V, Series 88V  Current - Output (Max)  Primary Winding(s)  Secondary Winding(s)  Dual  Secondary Winding(s)  Center Tap  Power - Max  Mounting Type  Through Hole  Termination Style  Size / Dimension  Transformers  Power - Transformers  Power - Transformers  Power - Max  Magnetics  Transformers  Power Transformers  Power - Transformers  Power - Max  12 VA  Mounting Type  Through Hole  PC Pin  Size / Dimension  63.50mm L x 50.80mm W		
Category  Transformers  Power Transformers  Package  Series  FP  Type  Laminated Core  Voltage - Primary  Voltage - Secondary (Full Load)  Parallel 44V, Series 88V  Current - Output (Max)  Parallel 260mA, Series 130mA  Primary Winding(s)  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  Mounting Type  Through Hole  Termination Style  Transformers  Power Tr	Manufacturer Part Number	FP88-130
Package Series FP Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 44V, Series 88V Current - Output (Max) Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Termination Style Power Transformers  - Query Transformers  Pussed  - Campa	Manufacturer	Triad Magnetics
Package - Series FP Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 44V, Series 88V Current - Output (Max) Parallel 260mA, Series 130mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style PP	Category	Transformers
Series Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 44V, Series 88V Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style  FP Laminated Core Laminated Core Laminated Core  Laminated Core  Laminated Core  115V, 230V  Parallel 24V, Series 88V  Dual  Parallel 260mA, Series 130mA  Pual  Dual  Through Hole PC Pin		Power Transformers
Type Laminated Core  Voltage - Primary 115V, 230V  Voltage - Secondary (Full Load) Parallel 44V, Series 88V  Current - Output (Max) Parallel 260mA, Series 130mA  Primary Winding(s) Dual  Secondary Winding(s) Dual  Center Tap No  Power - Max 12 VA  Mounting Type Through Hole  Termination Style PC Pin	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  Parallel 44V, Series 88V  Current - Output (Max)  Parallel 260mA, Series 130mA  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  12 VA  Mounting Type  Through Hole  Termination Style	Series	FP
Voltage - Secondary (Full Load)  Current - Output (Max)  Parallel 260mA, Series 130mA  Primary Winding(s)  Dual  Secondary Winding(s)  Center Tap  No  Power - Max  Mounting Type  Through Hole  Termination Style  Parallel 44V, Series 88V  Parallel 260mA, Series 130mA  Dual  Dual  Termination Style	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 12 VA Mounting Type Through Hole Termination Style Parallel 260mA, Series 130mA Dual  Dual Pual Powal Pow	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC Pin	Voltage - Secondary (Full Load)	Parallel 44V, Series 88V
Secondary Winding(s)DualCenter TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC Pin	Current - Output (Max)	Parallel 260mA, Series 130mA
Center TapNoPower - Max12 VAMounting TypeThrough HoleTermination StylePC Pin	Primary Winding(s)	Dual
Power - Max 12 VA  Mounting Type Through Hole  Termination Style PC Pin	Secondary Winding(s)	Dual
Mounting Type Through Hole Termination Style PC Pin	Center Tap	No
Termination Style PC Pin	Power - Max	12 VA
·	Mounting Type	Through Hole
Size / Dimension 63.50mm L x 50.80mm W	Termination Style	PC Pin
	Size / Dimension	63.50mm L x 50.80mm W
Height - Seated (Max) 26.97mm	Height - Seated (Max)	26.97mm
Voltage - Isolation 2000Vrms	Voltage - Isolation	2000Vrms
Weight 0.688 lb (312.07g)	Weight	0.688 lb (312.07g)
Report errors?		Report errors?

### FP88-130 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## FP88-130 Payment Methods



















## FP88-130 Shipping Methods













If you have any question about FP88-130, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com