

Heisener.com

FRCIR06R16S-4SWF80T109

FRCIR06R16S-4SWF80T109 Information

Part Number FRCIR06R16S-4SWF80T109

Manufacturer ITT Cannon, LLC

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 2POS STRGHT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FRCIR06R16S-4SWF80T109 Specifications

Manufacturer Part Number FRCIR06R16S-4SWF80T109 Manufacturer ITT Cannon, LLC Category Connectors, Interconnects Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 2 Shell Size - Insert 16S-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 13A		
Category Circular Connectors Package Package Package Plug, Female Sockets Number of Positions Package Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Fatures Flame Retardant Voltage - Rated Current Rating Circular Connectors MIL-DTL-5015, CIR Plug, Female Sockets NIL - Rose, Female Sockets Plug, Female Sockets Pl	Manufacturer Part Number	FRCIR06R16S-4SWF80T109
Package-SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert16S-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating13A	Manufacturer	ITT Cannon, LLC
Package - Series MIL-DTL-5015, CIR Connector Type Plug, Female Sockets Number of Positions 2 Shell Size - Insert 16S-4 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 113A	Category	Connectors, Interconnects
SeriesMIL-DTL-5015, CIRConnector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert16S-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating13A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions2Shell Size - Insert16S-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating13A	Package	-
Number of Positions2Shell Size - Insert16S-4Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeBayonet LockOrientationN (Normal)Ingress ProtectionEnvironment ProofShell Material, FinishAluminum Alloy, Black Zinc Cobalt PlatedContact FinishGoldFeaturesFlame RetardantVoltage - Rated900VAC, 1250VDCCurrent Rating13A	Series	MIL-DTL-5015, CIR
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Number of Positions	2
Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Shell Size - Insert	16S-4
Termination Crimp Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Shell Size, MIL	-
Fastening Type Bayonet Lock Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Environment Proof Shell Material, Finish Aluminum Alloy, Black Zinc Cobalt Plated Contact Finish Gold Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Termination	Crimp
Ingress Protection Environment Proof Shell Material, Finish Contact Finish Gold Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating Environment Proof Aluminum Alloy, Black Zinc Cobalt Plated Gold Flame Retardant 13A	Fastening Type	Bayonet Lock
Shell Material, Finish Contact Finish Gold Features Flame Retardant Voltage - Rated Ourrent Rating Aluminum Alloy, Black Zinc Cobalt Plated Gold Flame Retardant 13A	Orientation	N (Normal)
Contact Finish Gold Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Ingress Protection	Environment Proof
Features Flame Retardant Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Shell Material, Finish	Aluminum Alloy, Black Zinc Cobalt Plated
Voltage - Rated 900VAC, 1250VDC Current Rating 13A	Contact Finish	Gold
Current Rating 13A	Features	Flame Retardant
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	13A
-		Report errors?

FRCIR06R16S-4SWF80T109 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FRCIR06R16S-4SWF80T109 Payment Methods





















FRCIR06R16S-4SWF80T109 Shipping Methods













If you have any question about FRCIR06R16S-4SWF80T109, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com