

## **FRN-R-4 Information**

Heisener.com

Part Number FRN-R-4
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE TRON DUAL-ELEMENT CLASS RK5

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **FRN-R-4 Specifications**

Manufacturer Part NumberFRN-R-4ManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesFusetron? FRN-RFuse TypeCartridgeCurrent Rating4AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesFusetron? FRN-RFuse TypeCartridgeCurrent Rating4AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Manufacturer Part Number	FRN-R-4
Beckage Cartridge, Non-Standard Series Fusetron? FRN-R Fuse Type Cartridge Current Rating 4A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage County (Package / Case Cartridge, Non-Standard) Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesFusetron? FRN-RFuse TypeCartridgeCurrent Rating4AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Category	Circuit Protection
SeriesFusetron? FRN-RFuse TypeCartridgeCurrent Rating4AVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 4A Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge 250V Cartridge Capacity Lectrical Approvals CE, CSA, UL CE, CSA, UL Cortridge, Non-Standard Size / Dimension Cartridge, Non-Standard Size / Dimension Capacity Lectrical Capac	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  4A  4A  4A  4A  4A  250V  250V  CE, CSA  125V  Response Time Slow Clectrical, Industrial CE, CSA, UL  - CE, CSA, UL  - CE, CSA, UL  - CE, CSA, UL  - Cartridge, Non-Standard Size / Dimension  0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Series	Fusetron? FRN-R
Voltage Rating - AC  Voltage Rating - DC  125V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  250V  125V	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  125V  Response Time  Slow  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  COPITATION OF TABLET OF THE PACKAGE OF THE P	Current Rating	4A
Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Voltage Rating - AC	250V
Applications Electrical, Industrial  Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Voltage Rating - DC	125V
Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Country @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 20kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Approvals	CE, CSA, UL
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Mounting Type	Holder
·	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.560" Dia x 2.00" L (14.22mm x 50.80mm)
		Report errors?

### **FRN-R-4 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **FRN-R-4 Payment Methods**





















## **FRN-R-4 Shipping Methods**













If you have any question about FRN-R-4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com