

### FRS-R-350 Information

Heisener.com

Part Number FRS-R-350
Manufacturer Eaton

**Category** Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE TRON DUAL ELEMENT FUSE CLAS

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **FRS-R-350 Specifications**

Manufacturer Part NumberFRS-R-350ManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesFusetron? FRS-RFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.340" Dia x 11.630" L (59.44mm x 295.40mm)		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesFusetron? FRS-RFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.340" Dia x 11.630" L (59.44mm x 295.40mm)	Manufacturer Part Number	FRS-R-350
Beckage Cartridge, Non-Standard Series Fusetron? FRS-R Fuse Type Cartridge Current Rating 350A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 2.340" Dia x 11.630" L (59.44mm x 295.40mm)	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesFusetron? FRS-RFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC600VVoltage Rating - DC250VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.340" Dia x 11.630" L (59.44mm x 295.40mm)	Category	Circuit Protection
Fuse Type Cartridge Current Rating 350A  Voltage Rating - AC 600V  Voltage Rating - DC 250V  Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Stone  Cartridge Cartridge, Non-Standard Size / Dimension 230A  Source Cartridge (Cartridge, Non-Standard) Size / Dimension 230A  Size / Dimension 230A  Size / Dimension 230A  Size / Dimension 230A  Size / Siz		Electrical, Specialty Fuses
Fuse Type Current Rating 350A Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge A00V C00V Converting Capacity (Sp. 444mm x 295.40mm) And Converting Capacity (Sp. 444mm x 295.40mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC 250V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Signature 350A 600V CE, CSV END COV COV COV CE, CSA CE, CSA CE, CSA CE, CSA COV CARTRIGGE, Non-Standard Cartridge, Non-Standard Size / Dimension Signature	Series	Fusetron? FRS-R
Voltage Rating - AC  Voltage Rating - DC  250V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  250V  250V  250V  260V	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  250V  Response Time  Slow  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  COPIE Temperature  - Cartridge, Non-Standard  Size / Dimension  2.340" Dia x 11.630" L (59.44mm x 295.40mm)	Current Rating	350A
Response Time Applications Electrical, Industrial  Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Electrical, Industrial - CR, CSA HOU ARA AC, 20kA DC Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Electrical, Industrial - Cartridal  CE, CSA, UL - CE,	Voltage Rating - AC	600V
Applications Electrical, Industrial  Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 2.340" Dia x 11.630" L (59.44mm x 295.40mm)	Voltage Rating - DC	250V
Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 2.340" Dia x 11.630" L (59.44mm x 295.40mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 2.340" Dia x 11.630" L (59.44mm x 295.40mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension CE, CSA, UL - CHART CART CART CART CART CART CART CART C	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Cartridge, Non-Standard  2.340" Dia x 11.630" L (59.44mm x 295.40mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 2.340" Dia x 11.630" L (59.44mm x 295.40mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 2.340" Dia x 11.630" L (59.44mm x 295.40mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 2.340" Dia x 11.630" L (59.44mm x 295.40mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 2.340" Dia x 11.630" L (59.44mm x 295.40mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	2.340" Dia x 11.630" L (59.44mm x 295.40mm)
		Report errors?

### FRS-R-350 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### FRS-R-350 Payment Methods



















### FRS-R-350 Shipping Methods













If you have any question about FRS-R-350, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com