

#### FRS-R-7-1/2ID Information

Heisener.com

Part Number FRS-R-7-1/2ID

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE TRON DUAL ELEMENT FUSE CLAS

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# FRS-R-7-1/2ID Specifications

Manufacturer Part Number  Manufacturer  Eaton  Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cartridge, Non-Standard  Series  Fuse Type  Cartridge  Current Rating  7.5A  Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Electrical, Industrial  Features  Indicating  Class  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Electrical, Industrial  Features  RK5  Approvals  CE, CSA, UL  Operating Temperature		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesFusetron? FRS-RFuse TypeCartridgeCurrent Rating7.5AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Manufacturer Part Number	FRS-R-7-1/2ID
PackageCartridge, Non-StandardSeriesFusetron? FRS-RFuse TypeCartridgeCurrent Rating7.5AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesFusetron? FRS-RFuse TypeCartridgeCurrent Rating7.5AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Category	Circuit Protection
SeriesFusetron? FRS-RFuse TypeCartridgeCurrent Rating7.5AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating7.5AVoltage Rating - AC600VVoltage Rating - DC300VResponse TimeSlowApplicationsElectrical, IndustrialFeaturesIndicatingClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Package	Cartridge, Non-Standard
Current Rating  7.5A  Voltage Rating - AC  600V  Voltage Rating - DC  300V  Response Time  Slow  Applications  Electrical, Industrial  Features  Indicating  Class  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  7.5A  600V  CE, CSA  CU  300V  Response Time  Slow  Clectrical, Industrial  Electrical, Industrial  Clectrical, Industrial  Clectrical, Industrial  Slow  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  Operating Temperature  CE, CSA, U	Series	Fusetron? FRS-R
Voltage Rating - AC  Voltage Rating - DC  300V  Response Time  Slow  Applications  Electrical, Industrial  Indicating  Class  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  600V  300V  600V	Fuse Type	Cartridge
Voltage Rating - DC  Response Time  Slow  Applications  Electrical, Industrial  Features  Indicating  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  300V  300V  300V  300V  Slow  Slow  Electrical, Industrial  Indicating  RK5  CE, CSA, UL  CE, CSA, UL  Cartridge, Non-Standard  0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Current Rating	7.5A
Response Time  Applications  Electrical, Industrial  Features  Indicating  Class  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Slow  S	Voltage Rating - AC	600V
Applications Electrical, Industrial Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Voltage Rating - DC	300V
Features Indicating Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature	Features	Indicating
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  O.810" Dia x 3.00" L (20.57mm x 76.20mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Approvals	CE, CSA, UL
Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 0.810" Dia x 3.00" L (20.57mm x 76.20mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.810" Dia x 3.00" L (20.57mm x 76.20mm)
		Report errors?

#### FRS-R-7-1/2ID Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### FRS-R-7-1/2ID Payment Methods



















## FRS-R-7-1/2ID Shipping Methods













If you have any question about FRS-R-7-1/2ID, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com