



G2R-1A AC100/(110) Information

Heisener.com

Part Number G2R-1A AC100/(110)

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 10A 110V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-1A AC100/(110) Specifications

Manufacturer Part Number G2R-1A AC100/(110) Manufacturer Omron Electronics Inc-EMC Div Category Relays Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 10.6mA Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole		
CategoryRelaysPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.6mACoil Voltage110VACContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Manufacturer Part Number	G2R-1A AC100/(110)
Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 10.6mA Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Manufacturer	Omron Electronics Inc-EMC Div
Package - G2R Relay Type General Purpose Coil Type Non Latching Coil Current 10.6mA Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Trivous Contact Service (Sealed - Service Contact S	Category	Relays
SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.6mACoil Voltage110VACContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 10.6mA Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Package	-
Coil Type Non Latching Coil Current 10.6mA Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Series	G2R
Coil Current 10.6mA Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Coil Current	10.6mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Coil Voltage	110VAC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Turn On Voltage (Max)	88 VAC
Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole	Turn Off Voltage (Min)	33 VAC
Features Sealed - Flux Protection Mounting Type Through Hole	Operate Time	15ms
Mounting Type Through Hole	Release Time	10ms
	Features	Sealed - Flux Protection
	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

G2R-1A AC100/(110) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-1A AC100/(110) Payment Methods



















G2R-1A AC100/(110) Shipping Methods













If you have any question about G2R-1A AC100/(110), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com