

G2R-24-H-DC12

G2R-24-H-DC12 Information



Part Number	G2R-24-H-DC12	
Manufacturer	Omron Electronics Inc-EMC Div	
Category	Relays Power Relays, Over 2 Amps	
Description	RELAY GEN PURPOSE DPDT 3A 12V	
Package	-	
	For the pricing/inventory/lead time, please contact	
	us	
	Website: https://www.heisener.com	
	E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.

Part



G2R-24-H-DC12 Specifications

ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mAColtact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCQoperat Time5msRelease TimeSmsFeaturesSnel FullyMounting TypeThrough Hole		
CategoryRelaysPackage-Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mACoil ActorJUDCContact FormDPDT (2 Form C)Contact Rating (Current)34Switching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)4.4 VDCOperate Time5.msRelease Time5.msFeaturesSaled - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G2R-24-H-DC12
PackagePower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)1.8 VDCOperate Time15msRelease Time5msFaturesSaled - FullyMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)380VAC, 125VDC - MaxSwitching Voltage (Max)8.4 VDCTurn On Voltage (Max)1.8 VDCQerate Time5msRelease TimeSealed - FullyFaturesSealed - FullyMounting TypePC Pin	Category	Relays
SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)1.8 VDCTurn Off Voltage (Min)1.8 VDCOperate Time5msRelease TimeSealed - FullyMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.5 msRelease Time5msFeaturesSealed - FullyMounting TypePC Pin	Package	-
Coil TypeNon LachingCoil Current30mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Max)1.8 NDCOperate Time5msRelease TimeSealed - FullyFeaturesSealed - FullyMounting TypeCP inTermination StylePC in	Series	G2R
Coil Current30mACoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HolePermination StylePC Pin	Relay Type	General Purpose
Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease TimesSealed - FullyFeaturesForough HoleMounting TypePC Pin	Coil Type	Non Latching
Contact FormDPDT (2 Form C)Contact Rating (Current)3ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HolePermination StylePC Pin	Coil Current	30mA
Contact Rating (Current)3ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HolePermination StylePC Pin	Coil Voltage	12VDC
Switching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HolePermination StylePC Pin	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleYernination StylePC Pin	Contact Rating (Current)	3A
Turn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	8.4 VDC
Release Time5msFeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	1.8 VDC
FeaturesSealed - FullyMounting TypeThrough HoleTermination StylePC Pin	Operate Time	15ms
Mounting TypeThrough HoleTermination StylePC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Fully
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G2R-24-H-DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-24-H-DC12 Payment Methods



G2R-24-H-DC12 Shipping Methods



If you have any question about G2R-24-H-DC12, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com