

G2R-2A-DC24 Information



For Reference Only

Part Number G2R-2A-DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 5A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-2A-DC24 Specifications

| Manufacturer Part Number G2R-2A-DC24 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC | | |
|---|--------------------------|-------------------------------|
| Category Relays Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.8mA Coil Voltage Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 3.6 VDC | Manufacturer Part Number | G2R-2A-DC24 |
| Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC | Manufacturer | Omron Electronics Inc-EMC Div |
| Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC | Category | Relays |
| Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC | | Power Relays, Over 2 Amps |
| Relay Type Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 3.6 VDC | Package | - |
| Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC | Series | G2R |
| Coil Current 21.8mA Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC | Relay Type | General Purpose |
| Coil Voltage 24VDC Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC | Coil Type | Non Latching |
| Contact Form DPST (2 Form A) Contact Rating (Current) 5A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC | Coil Current | 21.8mA |
| Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC | Coil Voltage | 24VDC |
| Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC | Contact Form | DPST (2 Form A) |
| Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC | Contact Rating (Current) | 5A |
| Turn Off Voltage (Min) 3.6 VDC | Switching Voltage | 380VAC, 125VDC - Max |
| | Turn On Voltage (Max) | 16.8 VDC |
| Operato Timo | Turn Off Voltage (Min) | 3.6 VDC |
| Operate Time 13iis | Operate Time | 15ms |
| Release Time 5ms | Release Time | 5ms |
| Features Sealed - Flux Protection | Features | Sealed - Flux Protection |
| Mounting Type Through Hole | Mounting Type | Through Hole |
| Termination Style PC Pin | Termination Style | PC Pin |
| Report errors? | | Report errors? |

G2R-2A-DC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-2A-DC24 Payment Methods





















G2R-2A-DC24 Shipping Methods













If you have any question about G2R-2A-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com