

G6AK-474P-ST20-US DC3

G6AK-474P-ST20-US DC3 Information



For Reference Only

Part Number G6AK-474P-ST20-US DC3

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GENERAL PURPOSE 4PDT 2A 3V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G6AK-474P-ST20-US DC3 Specifications

Manufacturer Part Number G6AK-474P-ST20-US DC3 Manufacturer Omron Electronics Inc-EMC Div Category Relays Signal Relays, Up to 2 Amps Package - Series G6A Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current - Coil Voltage 3VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) - Operate Time 7ms Release Time 7ms Features - Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesG6ARelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current-Coil Voltage3VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.1 VDCTurn Off Voltage (Min)-Operate Time7msRelease Time7msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G6AK-474P-ST20-US DC3
Package - GeA Series G6A Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current - Coil Voltage 3VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) - Operate Time 7ms Release Time 7ms Features - Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package - G6A Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current - Coil Voltage 3VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) - Operate Time 7ms Release Time 7ms Release Time 7ms Features - Mounting Type Through Hole Termination Style PC Pin	Category	Relays
SeriesG6ARelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current-Coil Voltage3VDCContact Form4PDT (4 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.1 VDCTurn Off Voltage (Min)-Operate Time7msRelease Time7msFeatures-Mounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current - Coil Voltage 3VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) - Operate Time 7ms Release Time 7ms Release Time 7ms Features - Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil Type Coil Current - Coil Voltage 3VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) - Operate Time 7ms Release Time 7ms Features - Mounting Type Through Hole Termination Style Latching, Dual Coil - Contact Rating, Dual Coil - Name - Turn Off - Turn Off - Turn Cf) - Turn Off -	Series	G6A
Coil Current Coil Voltage 3VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) - Operate Time 7ms Release Time 7ms Features - Mounting Type Through Hole Termination Style - Contact Rating (Current) 2A - APDT (4 Form C) - APD	Relay Type	General Purpose
Coil Voltage 3VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) - Operate Time 7ms Release Time 7ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Type	Latching, Dual Coil
Contact Form 4PDT (4 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) - Operate Time 7ms Release Time 7ms Release Time 7ms Features - Mounting Type Through Hole Termination Style PC Pin	Coil Current	-
Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 7urn Off Voltage (Min) Operate Time 7ms Release Time 7ms Features - Mounting Type Through Hole Termination Style	Coil Voltage	3VDC
Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) - Operate Time 7ms Release Time 7ms Features - Mounting Type Through Hole Termination Style PC Pin	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time 7ms Release Time 7ms Features - Mounting Type Through Hole Termination Style	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 7ms Release Time 7ms Features - Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	250VAC, 220VDC - Max
Operate Time 7ms Release Time 7ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	2.1 VDC
Release Time 7ms Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	-
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	7ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	7ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G6AK-474P-ST20-US DC3 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G6AK-474P-ST20-US DC3 Payment Methods



















G6AK-474P-ST20-US DC3 Shipping Methods













If you have any question about G6AK-474P-ST20-US DC3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com