

G6B-1177P-ND-US-P6B DC5 Information

| Heisener.com | G6B-1177P-ND-US-P6B DC5 Omron Electronics Inc-EMC Div Relays Power Relays, Over 2 Amps RELAY GENERAL PURPOSE SPST 8A 5V - For the pricing/inventory/lead time, please contact | |
|--------------------|---|-----------------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G6B-1177P-ND-US-P6B DC5 Specifications

| Manufacturer Part NumberGGB-1177P-ND-US-PGB DC5ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPackage-SeriesGGBRelay TypeGeneral PurposeCoil TypeMon LatchingCoil Current40mACotact FormSPST-NO (I Form A)Contact Rating (Current)SPST-NO (I Form A)Switching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Of Voltage (Max)0.5 VDCQuerta Time10msRelease TimeIomsRelease TimeSeal - Fully, Socket IncludedMouning TypeTurough HolePart MarkScore TormanFeaturesPC Pin | | |
|--|--------------------------|---------------------------------|
| CategoryRelaysCategoryRelays, Over 2 AmpsPackage-PackageGBRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mACoil CurrentSVDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)0.5 VDCCoperate Time10msRelease Time10msFeaturesSealed - Fully, Socket IncludedMounting TypeThrough HoleFermination StylePC Pin | Manufacturer Part Number | G6B-1177P-ND-US-P6B DC5 |
| Power Relays, Over 2 AmpsPackage-SeriesG6BRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mAColtarterSVDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCOperate Time10msRelease Time10msFeaturesSealed - Fully, Socket IncludedMounting TypeThrough HoleTermination StylePC Pin | Manufacturer | Omron Electronics Inc-EMC Div |
| Package-SeriesG6BRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mACoil VoltageSVDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time10msFeaturesScaled - Fully, Socket IncludedMounting TypeCring HoleTermination StylePC Pin | Category | Relays |
| SeriesG6BRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)0.5 VDCOperate Time10msRelease Time10msFeaturesSealed - Fully, Socket IncludedMounting TypePC Pin | | Power Relays, Over 2 Amps |
| Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)0.5 VDCOperate Time10msRelease Time10msFeaturesSealed - Fully, Socket IncludedMounting TypePC Pin | Package | - |
| Coil TypeNon LatchingCoil Current40mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Max)0.5 VDCOperate Time10msRelease TimeSealed - Fully, Socket IncludedFeaturesThrough HoleMounting TypePC Pin | Series | G6B |
| Coil Current40mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time10msFeaturesSealed - Fully, Socket IncludedMounting TypeThrough HolePerinnation StylePC Pin | Relay Type | General Purpose |
| Coil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time10msFeaturesSeled - Fully, Socket IncludedMounting TypeThrough HoleTermination StylePC Pin | Coil Type | Non Latching |
| Contact FormSPST-NO (1 Form A)Contact Form8ASwitching (Current)880VAC, 125VDC - MaxSwitching Voltage (Max)3.5 VDCTurn On Voltage (Max)0.5 VDCOperate Time0.5 VDCRelease Time10msFeaturesSealed - Fully, Socket IncludedMounting TypeThrough HoleYernination StylePC Pin | Coil Current | 40mA |
| Contact Rating (Current)8ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time10msFeaturesSealed - Fully, Socket IncludedMounting TypeThrough HoleYernination StylePC Pin | Coil Voltage | 5VDC |
| Switching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time10msFeaturesSealed - Fully, Socket IncludedMounting TypeThrough HoleTermination StylePC Pin | Contact Form | SPST-NO (1 Form A) |
| Turn On Voltage (Max)3.5 VDCTurn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time10msFeaturesSealed - Fully, Socket IncludedMounting TypeThrough HoleTermination StylePC Pin | Contact Rating (Current) | 8A |
| Turn Off Voltage (Min)0.5 VDCOperate Time10msRelease Time10msFeaturesSealed - Fully, Socket IncludedMounting TypeThrough HoleTermination StylePC Pin | Switching Voltage | 380VAC, 125VDC - Max |
| Operate Time10msRelease Time10msFeaturesSealed - Fully, Socket IncludedMounting TypeThrough HoleTermination StylePC Pin | Turn On Voltage (Max) | 3.5 VDC |
| Release Time10msFeaturesSealed - Fully, Socket IncludedMounting TypeThrough HoleTermination StylePC Pin | Turn Off Voltage (Min) | 0.5 VDC |
| FeaturesSealed - Fully, Socket IncludedMounting TypeThrough HoleTermination StylePC Pin | Operate Time | 10ms |
| Mounting TypeThrough HoleTermination StylePC Pin | Release Time | 10ms |
| Termination Style PC Pin | Features | Sealed - Fully, Socket Included |
| | Mounting Type | Through Hole |
| Report errors? | Termination Style | PC Pin |
| | | Report errors? |

G6B-1177P-ND-US-P6B DC5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about G6B-1177P-ND-US-P6B DC5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com