

G6K-2F-RF-S-TR03 DC4.5 Information

	Manufacturer	G6K-2F-RF-S-TR03 DC4.5 Omron Electronics Inc-EMC Div	
www.heisener.com	Category	Relays Signal Relays, Up to 2 Amps	
23. 11	Description	RELAY RF DPDT 1A 4.5V	
	Package	-	
		For the pricing/inventory/lead time, please contact	(=)//6/% 374
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G6K-2F-RF-S-TR03 DC4.5 Specifications

Manufacturer Part Number G6K-2F-RF-S-TR03 DC4.5 Manufacturer Omron Electronics Inc-EMC Div Category Relays Otagory Baigan Relays, Up to 2 Amps Package - Series G6K-RF Relay Type RF Coil Type Non Latching Coil Current 3.2mA Coil Acting Current ASVDC Cotact Form DPDT (2 Form C) Cotact Rating (Current) IA Switching Voltage ISVAC, 60VDC - Max Turn On Voltage (Max) Soft SOC Operator Time Sms Release Time Sms Features IGHZ Mounting Type Gull Wing		
CategoryRelaysCategoryRelaysPackage-Package-SeriesG6K-RFRelay TypeRFCoil TypeNon LatchingCoil Current23.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage3.6 VDC - MaxTurn On Voltage (Max)0.45 VDC - MaxQuerate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountFermination StyleSurface Mount	Manufacturer Part Number	G6K-2F-RF-S-TR03 DC4.5
Signal Relays, Up to 2 AmpsPackage-SeriesG6K-RFRelay TypeRFCoil TypeNon LatchingCoil Current23.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.6 VDCOperate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleSurface Mount	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG6K-RFRelay TypeRFCoil TypeNon LatchingCoil Current23.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.6 VDCOperate TimeMassRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Category	Relays
SeriesG6K-RFRelay TypeRFCoil TypeNon LatchingCoil Current23.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)0.45 VDCOperate Time3msRelease Time1 GHzFeatures1 GHzMounting TypeGuil Wing		Signal Relays, Up to 2 Amps
Relay TypeRFCoil TypeNon LatchingCoil Current23.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.6 VDCOperate TimeManRelease Time3msFeatures1 GHzMounting TypeGull Wing	Package	-
Coil TypeNon LatchingCoil Current23.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)0.45 VDCOperate Time3msRelease Time1 GHzFeatures1 GHzMounting TypeGuil Wing	Series	G6K-RF
Coil Current23.2mACoil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)0.45 VDCOperate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Relay Type	RF
Coil Voltage4.5VDCContact FormDPDT (2 Form C)Contact Rating (Current)IASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)0.45 VDCOperate Time3msRelease Time1 GHzFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Coil Type	Non Latching
Contact FormDPDT (2 Form C)Contact FormIASwitching (Current)125VAC, 60VDC - MaxTurn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)0.45 VDCOperate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Coil Current	23.2mA
Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)0.45 VDCOperate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Coil Voltage	4.5VDC
Switching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)0.45 VDCOperate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)3.6 VDCTurn Off Voltage (Min)0.45 VDCOperate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Contact Rating (Current)	1A
Turn Off Voltage (Min)0.45 VDCOperate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Switching Voltage	125VAC, 60VDC - Max
Operate Time3msRelease Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Turn On Voltage (Max)	3.6 VDC
Release Time3msFeatures1 GHzMounting TypeSurface MountTermination StyleGull Wing	Turn Off Voltage (Min)	0.45 VDC
Features1 GHzMounting TypeSurface MountTermination StyleGull Wing	Operate Time	3ms
Mounting TypeSurface MountTermination StyleGull Wing	Release Time	3ms
Termination Style Gull Wing	Features	1 GHz
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
		Report errors?

G6K-2F-RF-S-TR03 DC4.5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G6K-2F-RF-S-TR03 DC4.5 Payment Methods



If you have any question about G6K-2F-RF-S-TR03 DC4.5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com