

GCC20DREI

GCC20DREI Information

Heisener.com	Part Number Manufacturer Category Description Package	GCC20DREI Sullins Connector Solutions Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors CONN EDGE DUAL FMALE 40POS 0.100 - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



GCC20DREI Specifications

ManufacturerSullins Connector SolutionsCategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact FinishSolder Eyelet(s)Contact Finish ThicknessGoldContact TypeGoldContact TypeSille IlowsContact TypeSille IlowsCo	_	
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeSolder SectoreContact TypeSolder SectoreContact TypeSolder SectoreContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Manufacturer Part Number	GCC20DREI
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact Material90Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsColorBlackFlange Feature- 55°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsContact TypeFull BellowsContact TypeFull BellowsFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact Finish Thickness30µin (0.76µm)Contact Finish ThicknessSoljain (0.76µm)Contact TypeFeallellowsContact TypeSolder ScollentContact TypeSoljain (0.76µm)Contact TypeFeallellowsContact TypeSoljain (0.76µm)Contact TypeSoljain (0.76µm)ColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact Finish ThicknessGoldContact Finish ThicknessGoldContact TypeFull BellowsColorBackFaquere Feature-Operating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountContact MaterialSolder Eyelet(s)Contact FinishGoldContact TypeGoldContact TypeSujun (0.76µm)ColorBlackFalareeTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 125°C	Series	-
Number of Positions/Bay/Row20Number of Positions40Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 40 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Gold Contact Finish Gold Contact Type Full Bellows Color Black Flange Feature - Op Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeFull BellowsColorBlackFlange Feature-50°C ~ 125°C	Number of Positions/Bay/Row	20
Number of Rows2Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions	40
Pitch0.100" (2.54mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 125°C	Number of Rows	2
Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Mounting Type	Panel Mount
Contact FinishGoldContact Finish Thickness $30\mu in (0.76\mu m)$ Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Termination	Solder Eyelet(s)
Contact Finish Thickness30µin (0.76µm)Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColorBlackFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish	Gold
Color Black Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	30µin (0.76µm)
Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Black
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	$-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$
		Report errors?

GCC20DREI Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

GCC20DREI Payment Methods



GCC20DREI Shipping Methods



If you have any question about GCC20DREI, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com